

z/OS



Language Environment Run-Time Application Migration Guide

z/OS



Language Environment Run-Time Application Migration Guide

Note

Before using this information and the product it supports, be sure to read the general information under “Notices” on page 67.

This edition applies to Language Environment® in version 1, release 12, modification 0 of z/OS (product number 5694-A01), and to subsequent releases and modifications until otherwise indicated in new editions.

This edition replaces GA22-7565-10.

© **Copyright IBM Corporation 1991, 2010.**

US Government Users Restricted Rights – Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

Contents

Tables	v
-------------------------	----------

About this document	vii
Using your documentation	viii
Where to find more information	ix
Information updates on the web	ix
The z/OS Basic Skills Information Center	ix

How to send your comments to IBM	xi
If you have a technical problem.	xi

Summary of changes	xiii
-------------------------------------	-------------

Chapter 1. Planning to migrate to Language Environment	1
Checklist for migration	1
Planning to link and run with Language Environment	3

Chapter 2. Migrating from another Language Environment release.	5
Migration actions required for each release	5
Migration considerations for Language Environment in z/OS V1R12	6
Setting run-time options as overrideable or nonoverrideable	6
Changes to the Language Environment run-time options report when issuing D CEE.	7
Removal of conversion table source code	8
Changes to the CICS CLER run-time options report.	9
Migration considerations for Language Environment in z/OS V1R11	10
Changes to the HEAPCHK run-time option	10
Changes to Binary and Decimal Floating-Point support in the CICS Environment	10
Migration considerations for Language Environment in z/OS V1R10	11
HEAPOOLS Consideration:	11
Health Check - check(ibmcee,cee_using_le_parmlib):	11
Changes to CEEDOPT location:.	11
Changes to data exceptions:	11
Changes to PL/I stream I/O behavior:	11
Changes to Venezuela and Malta currency:	12
Migration considerations for Language Environment in z/OS V1R9	12
CEEDUMP run-time option added	12
Changes to Language Environment dump output, options reports and storage reports.	12
Changes to CELQPIPI	13
Changes to the CLER transaction	13
Changes to XPLINK under LRR	13
Heap Pools Consideration:	13

Changes to messages	14
-------------------------------	----

Chapter 3. Migrating from other run-time environments	15
Compatibility with previous run-time libraries.	15
Migrating ILC applications to Language Environment	16
Migrating C routines to Language Environment	17
Migrating COBOL programs to Language Environment	17
Migrating Fortran routines to Language Environment	17
Migrating PL/I routines to Language Environment	18
Migrating assembler programs to Language Environment	19

Chapter 4. Choosing run-time options for compatible behavior	21
Differences between run-time options.	21
C and Language Environment run-time options comparison	21
COBOL and Language Environment run-time options comparison.	22
Fortran and Language Environment run-time options comparison.	24
PL/I and Language Environment run-time options comparison.	25
Run-time option summary and recommendations	26

Chapter 5. Other HLL migration considerations	33
C considerations.	33
Standard streams	33
Passing command line parameters.	33
User exits	33
Time functions	33
Load modules that invoke a Debugging Tool	34
Prefix of perror() and strerror() messages in C.	34
AMODE errors from ILCs	34
PL/I considerations	34
Dumps	34
Condition handling.	34
User exits	35
SYSPRINT.	35
Format and content of messages	35
VisualAge PL/I for OS/390 object compatibility	36
General considerations	36
Return and reason codes	36
Storage reports	36
Stream I/O	36

Appendix A. Language Environment-enabled vendor tools and application packages	37
---	-----------

IBM Corporation	38
z/OS	38
Products	38
Action Software International	42
ADPAC Corp.	43
Advantis	43
Advisor Technology Services	43
Alltel Corp.	44
American Software, Inc.	44
ANSYS, Inc.	44
Applications Software, Inc.	44
Candle	45
Chicago-Soft, Ltd.	45
CHI/COR Information Management, Inc	46
CINCOM Systems, Inc.	46
Computer Associates International, Inc.	46
Computer Corporation of America	49
Compuware Corp.	49
Comshare, Inc.	49
Data Kinetics, Ltd.	50
Deluxe Corp.	50
Diversified Software Systems, Inc.	50
Document Sciences Corporation	51
Early, Cloud Solution Unit of IBM.	51
Edge Information Group, Inc.	51
EWO Software, Inc..	52
Geac Host Technologies	52
HBO & Co.	52
Hogan Systems, Inc.	53
HNC Software	53
Infodata Systems, Inc.	53
Information Builders, Inc..	54
Information Retrieval Companies, Inc. (IRC Inc.)	54
Information Systems Of America, Inc.	54
Integral, Inc.	55
Intersolv	55
ISOGON, Inc..	55
Lotus Development Corporation (An IBM Company).	55
Macro 4 Inc.	56
MARBLE Computer, Inc.	56

Merrill Consultants	56
Micro Focus, Inc.	57
Mobius Management Systems, Inc.	57
National Technology Transfer Center	57
Panarama Software.	57
Pegasystems, Inc.	58
Peregrine Systems, Inc.	58
Pitney Bowes.	58
Platinum Technology	59
Prince Software, Inc.	59
Proginet	59
Rocket Software, Inc.	60
SAS Institute	60
Seer Technologies, Inc..	60
Serena Software International	60
Software AG	61
Software Engineers of America (SEA).	62
Sterling Software	62
Stonehouse & Co.	63
Syncsort, Inc.	63
Texas Instruments, Inc.	63
Viasoft, Inc.	64
Walker Interactive Systems	64

Appendix B. Accessibility 65

Using assistive technologies	65
Keyboard navigation of the user interface	65
z/OS information	65

Notices 67

Policy for unsupported hardware	69
Programming Interface information	69
Trademarks	69

Bibliography 71

Language Products Publications	71
Related Publications	72

Index 75

Tables

1. How to Use z/OS Language Environment Publications	viii	7. COBOL and Language Environment Run-Time Options	22
2. ILC Compatibility Exceptions	16	8. Fortran and Language Environment Run-Time Options	24
3. COBOL Compatibility Exceptions	17	9. PL/I and Language Environment Run-Time Options	25
4. Fortran Compatibility Exceptions	17	10. Language Environment Run-Time Options, Defaults, and Recommendations	26
5. PL/I Compatibility Exceptions	18		
6. C and Language Environment Run-Time Options	21		

About this document

This document supports z/OS (5694-A01).

IBM® z/OS Language Environment (also called Language Environment) provides common services and language-specific routines in a single run-time environment for C, C++, COBOL, Fortran (z/OS only; no support for z/OS UNIX System Services or CICS®), PL/I, and assembler applications. It offers consistent and predictable results for language applications, independent of the language in which they are written.

Language Environment is the prerequisite run-time environment for applications generated with the following IBM compiler products:

- z/OS XL C/C++ (feature of z/OS)
- z/OS C/C++
- OS/390 C/C++
- C/C++ for MVS/ESA
- C/C++ for z/VM
- XL C/C++ for z/VM
- AD/Cycle® C/370™
- VisualAge for Java, Enterprise Edition for OS/390
- Enterprise COBOL for z/OS
- Enterprise COBOL for z/OS and OS/390
- COBOL for OS/390 & VM
- COBOL for MVS & VM (formerly COBOL/370)
- Enterprise PL/I for z/OS
- Enterprise PL/I for z/OS and OS/390
- VisualAge PL/I
- PL/I for MVS & VM (formerly PL/I MVS™ & VM)
- VS FORTRAN and FORTRAN IV (in compatibility mode)

Although not all compilers listed are currently supported, Language Environment supports the compiled objects that they created.

Language Environment supports, but is not required for, an interactive debug tool for debugging applications in your native z/OS environment.

Debug Tool is also available as a standalone product. Debug Tool Utilities and Advanced Functions is also available. For more information, see <http://www.ibm.com/software/awdtools/debugtool/>.

Language Environment supports, but is not required for, VS FORTRAN Version 2 compiled code (z/OS only).

Language Environment consists of the common execution library (CEL) and the run-time libraries for C/C++, COBOL, Fortran, and PL/I.

For more information on VisualAge for Java, Enterprise Edition for OS/390, program number 5655-JAV, see the product documentation.

This book provides an overview of the steps z/OS customers must take to migrate applications for use with z/OS Language Environment. These customers may not necessarily be migrating to a new language compiler.

This book is written for application developers. Familiarity with the run-time libraries of the different languages, and an understanding of the basics of linking and running applications, are assumed.

The information in this book will not provide a comprehensive guide to the migration process; rather, it is designed to help you create a broad migration strategy. This book will help you identify which modules can be migrated first, and which will require relinking or recompiling. It also explains how to use Language Environment run-time options to achieve behavior that is compatible with your old modules. For more detailed information about migration topics such as upgrading source code and load module compatibility, see one of the following manuals:

- *z/OS XL C/C++ Compiler and Run-Time Migration Guide for the Application Programmer*
- *IBM C for VM/ESA Compiler and Run-Time Migration Guide*
- *Enterprise COBOL for z/OS, V4R2, Compiler and Runtime Migration Guide, GC23-8527, or Enterprise COBOL for z/OS, V3R4, Compiler and Runtime Migration Guide, GC27-1409.*
- *VisualAge PL/I for OS/390 Compiler and Run-Time Migration Guide*
- *Enterprise PL/I for z/OS, V3R9, Migration Guide or PL/I for MVS & VM Compiler and Run-Time Migration Guide*
- *Fortran Run-Time Migration Guide*

Using your documentation

The publications provided with Language Environment are designed to help you:

- Manage the run-time environment for applications generated with a Language Environment-conforming compiler.
- Write applications that use the Language Environment callable services.
- Develop interlanguage communication applications.
- Customize Language Environment.
- Debug problems in applications that run with Language Environment.
- Migrate your high-level language applications to Language Environment.

Language programming information is provided in the supported high-level language programming manuals, which provide language definition, library function syntax and semantics, and programming guidance information.

Each publication helps you perform different tasks, some of which are listed in Table 1. All books are available in printable (PDF) and BookManager softcopy formats. For a complete list of publications that you may need, see “Bibliography” on page 71.

Table 1. How to Use z/OS Language Environment Publications

To ...	Use ...
Evaluate Language Environment	<i>z/OS Language Environment Concepts Guide</i>
Plan for Language Environment	<i>z/OS Language Environment Concepts Guide</i>
	<i>z/OS Language Environment Run-Time Application Migration Guide</i>
Install Language Environment	<i>z/OS Program Directory</i>
Customize Language Environment	<i>z/OS Language Environment Customization</i>

Table 1. How to Use z/OS Language Environment Publications (continued)

To ...	Use ...
Understand Language Environment program models and concepts	<i>z/OS Language Environment Concepts Guide</i>
	<i>z/OS Language Environment Programming Guide</i>
	<i>z/OS Language Environment Programming Guide for 64-bit Virtual Addressing Mode</i>
Find syntax for Language Environment run-time options and callable services	<i>z/OS Language Environment Programming Reference</i>
Develop applications that run with Language Environment	<i>z/OS Language Environment Programming Guide and your language programming guide</i>
Debug applications that run with Language Environment, diagnose problems with Language Environment	<i>z/OS Language Environment Debugging Guide</i>
Get details on run-time messages	<i>z/OS Language Environment Run-Time Messages</i>
Develop interlanguage communication (ILC) applications	<i>z/OS Language Environment Writing Interlanguage Communication Applications and your language programming guide</i>
Migrate applications to Language Environment	<i>z/OS Language Environment Run-Time Application Migration Guide</i> and the migration guide for each Language Environment-enabled language

Where to find more information

For an overview of the information associated with z/OS, see *z/OS Information Roadmap*.

Information updates on the web

For the latest information updates that have been provided in PTF cover letters and documentation APARs for z/OS[®], see the online document at: http://publibz.boulder.ibm.com/cgi-bin/bookmgr_OS390/Shelves/ZDOCAPAR

This document is updated weekly and lists documentation changes before they are incorporated into z/OS publications.

The z/OS Basic Skills Information Center

The z/OS Basic Skills Information Center is a Web-based information resource intended to help users learn the basic concepts of z/OS, the operating system that runs most of the IBM mainframe computers in use today. The Information Center is designed to introduce a new generation of Information Technology professionals to basic concepts and help them prepare for a career as a z/OS professional, such as a z/OS system programmer.

Specifically, the z/OS Basic Skills Information Center is intended to achieve the following objectives:

- Provide basic education and information about z/OS without charge
- Shorten the time it takes for people to become productive on the mainframe
- Make it easier for new people to learn z/OS.

To access the z/OS Basic Skills Information Center, open your Web browser to the following Web site, which is available to all users (no login required):
<http://publib.boulder.ibm.com/infocenter/zoslnctr/v1r7/index.jsp>

How to send your comments to IBM

We appreciate your input on this publication. Feel free to comment on the clarity, accuracy, and completeness of the information or give us any other feedback that you might have.

Use one of the following methods to send us your comments:

1. Send an email to mhvrcfs@us.ibm.com
2. Visit the Contact z/OS web page at <http://www.ibm.com/systems/z/os/zos/webqs.html>
3. Mail the comments to the following address:
IBM Corporation
Attention: MHVRCFS Reader Comments
Department H6MA, Building 707
2455 South Road
Poughkeepsie, NY 12601-5400
U.S.A.
4. Fax the comments to us as follows:
From the United States and Canada: 1+845+432-9405
From all other countries: Your international access code +1+845+432-9405

Include the following information:

- Your name and address
- Your email address
- Your telephone or fax number
- The publication title and order number:
z/OS V1R12.0 Language Environment Run-Time Application Migration
Guide
GA22-7565-11
- The topic and page number related to your comment
- The text of your comment.

When you send comments to IBM, you grant IBM a nonexclusive right to use or distribute your comments in any way it believes appropriate without incurring any obligation to you.

IBM or any other organizations will only use the personal information that you supply to contact you about the issues that you submit.

If you have a technical problem

Do not use the feedback methods listed above. Instead, do one of the following:

- Contact your IBM service representative
- Call IBM technical support
- Visit the IBM zSeries support web page at <http://www.ibm.com/systems/z/support/>

Summary of changes

Summary of changes for GA22-7565-11 z/OS Version 1 Release 12

The book contains information previously presented in *z/OS Language Environment Run-Time Migration Guide*, GA22-7565-10, which supports z/OS Version 1 Release 11.

New information

- “Setting run-time options as overrideable or nonoverrideable” on page 6 describes the change in setting run-time options as overrideable or nonoverrideable in the CEEPRMxx parmlib member.
- “Changes to the Language Environment run-time options report when issuing D CEE” on page 7 describes the changes made to the run-time options report when a D CEE command is issued.
- “Removal of conversion table source code” on page 8 describes removal of the source code for conversion tables.
- “Changes to the CICS CLER run-time options report” on page 9 describes the change to the run-time options report displayed from the CICS CLER transaction.

Changed information

- The "Readers' Comments - We'd Like to Hear from You" section at the back of this publication has been replaced with a new section “How to send your comments to IBM” on page xi. The hardcopy mail-in form has been replaced with a page that provides information appropriate for submitting readers comments to IBM.

This book contains terminology, maintenance, and editorial changes. Technical changes or additions to the text and illustrations are indicated by a vertical line to the left of the change.

You may notice changes in the style and structure of some content in this book — for example, headings that use uppercase for the first letter of initial words only, and procedures that have a different look and format. The changes are ongoing improvements to the consistency and retrievability of information in our books.

Summary of changes for GA22-7565-10 z/OS Version 1 Release 11

The book contains information previously presented in *z/OS Language Environment Run-Time Migration Guide*, GA22-7565-09, which supports z/OS Version 1 Release 10.

New information

Changed information

- HEAPCHK(ON,0,0,10) changed to the new default values (HEAPCHK(OFF,1,0,0,0,1024,0,1024,0)).
- Binary and Decimal Floating-Point support in the CICS Environment.

**Summary of changes
for GA22-7565-09
z/OS Version 1 Release 10**

The book contains information previously presented in *z/OS Language Environment Run-Time Migration Guide*, GA22-7565-08, which supports z/OS Version 1 Release 9.

New information

Changed information

- “HEAPPOOLS Consideration:” on page 11 contains a description of the changes that AMODE64 applications and processes will no longer ignore the HEAPPOOLS run-time option.
- “Changes to CEEDOPT location:” on page 11 contains a description of the changes of the installation-wide-run-time-option module CEEDOPT moved from CEEBINIT to CEEPLPKA load module.
- “Changes to Venezuela and Malta currency:” on page 12 contains a description of the changes for Venezuela and Malta currency.

Chapter 1. Planning to migrate to Language Environment

This topic provides a checklist to help you plan the migration of your applications to the Language Environment run-time environment for the first time.

For more detailed information about migration considerations, see Chapter 3, “Migrating from other run-time environments,” on page 15. If you are migrating from a previous release of Language Environment, you should review the information in Chapter 2, “Migrating from another Language Environment release,” on page 5.

Checklist for migration

Each task in the following checklist is recommended; you should perform each task in the order shown.

1. Learn about Language Environment.

Ensure that you and other application programmers who will be involved in the migration effort are familiar with the features of Language Environment and the differences between your current run-time environment and the Language Environment run-time environment. You can get information about Language Environment from publications such as:

- *z/OS Language Environment Customization*
- *z/OS Language Environment Concepts Guide*

2. Take an inventory of the applications and vendor products you intend to run with Language Environment.

- C, C++, COBOL, Fortran, PL/I, or Assembler programs

For each program you intend to move to the Language Environment run-time environment, obtain the following information:

- Version and release of the compiler that generated the program
 - Which COBOL programs were compiled with RES and which with NORES
 - Run-time options used and how they were specified
 - Which PL/I programs use the shared library and which ones do not
 - Which programs call, or are called by, assembler programs
 - Which applications contain interlanguage communication (ILC)
 - Which programs are used with CICS, IMS[™], DB2[®], or other subsystems
 - Control statements used
 - Frequency and types of abends
 - Test cases required and available
 - Amount of storage used
 - Frequency of execution of reusable or common modules
 - Program execution time (processor (CPU) and elapsed)
- Vendor tools, packages, and products
 - Ensure that all vendor tools, packages, and products run with Language Environment; any source code for the packages must also be compatible with your Language Environment-conforming compiler.
 - Ensure that any vendor code generators generate code that is compatible with your Language Environment-conforming compiler.
 - Ensure that vendor development tools and debuggers will not issue their own ESPIE or ESTAE, as Language Environment must get control first.

3. Prioritize programs.

Determine the effort required to migrate each program and the order in which you will migrate them. Each program will require some level of effort to migrate, ranging from minimal testing to a code rewrite. Using the information from your inventory analysis, determine if each program:

- Requires minimum, moderate, or extensive testing
- Runs with Language Environment without change
- Requires relinking with Language Environment
- Must be recompiled with a Language Environment-conforming compiler, without change to the source code
- Requires changes to the source code
- Does not run with Language Environment

After you have determined the effort required to migrate each load module, list your programs in the order you want to move them to Language Environment. You should consider the importance of each program and how often it is used.

You should migrate applications that contain ILC after you have migrated any applications that contain only C, C++, COBOL, Fortran, or PL/I. (An application that contains assembler, but is otherwise created from one language, is not considered an ILC application in this information.) For information about compatibility considerations for ILC applications, see “Migrating ILC applications to Language Environment” on page 16.

4. Install Language Environment.

Perform the following tasks, which can be done concurrently:

- Change default run-time options as appropriate.

To ensure that the Language Environment run-time results are compatible with your current run-time results, you will need to change some of the default settings for the run-time options. For a list of recommended settings, see “Run-time option summary and recommendations” on page 26.

- Assess storage requirements.

Storage requirements may be larger for Language Environment than for your current run-time environment. During conversion, you might need DASD for the Language Environment run-time library and for the run-time library that you are currently using. For information about Language Environment DASD requirements, see *z/OS Program Directory*.

Virtual storage requirements for placing library routines above or below the 16M line may also increase, depending on which Language Environment storage options you specify. See “Run-time option summary and recommendations” on page 26 for recommended settings.

- Determine how to phase-in the Language Environment run-time environment using a STEPLIB approach or by adding Language Environment to the LNKLST.

Using the STEPLIB approach, you can gradually phase-in the Language Environment run-time environment. When you use STEPLIB statements to specify the Language Environment run-time environment, you can phase-in one region (CICS or IMS), batch (group of applications), or user (TSO) at a time. Although using STEPLIB means changing JCL, a gradual conversion can be easier than moving all of your applications at one time.

When you add Language Environment to the LNKLST, it is available to all of your applications. Ensure all applications are functioning correctly with Language Environment before adding Language Environment to your LNKLST. You might consider temporarily adding Language Environment to the LNKLST until you have confirmed the applications work as intended.

5. Set up a regression testing procedure.

To ensure that the Language Environment run-time results are compatible with your current run-time results, you will need to perform regression tests on all the programs you migrate. Run your applications in parallel with your current run-time environment and with the Language Environment run-time environment to confirm that the results are the same. You can temporarily add Language Environment to the LINKLST to accomplish this. When your applications are running with Language Environment in a test environment, you should take performance measurements, especially on any time-critical or response-critical applications.

6. Move applications into production.

When your testing shows the entire application (or group of applications, if running more than one application in an IMS region or under TSO) runs as expected, you can move the entire unit over to production use. However, if an unexpected error occurs, you may need to perform one of the following steps:

- On z/OS systems, run the previous version of your application as a substitute.
- Under DB2, CICS, and IMS, return to the last commit point and then continue processing from that point using the previous version of the program. For DB2, use an SQL ROLLBACK WORK statement.
- For batch applications, use the backup and restore facilities at your site to recover.

After you move your applications to production use with the Language Environment run-time environment, monitor your applications to ensure that they continue to work properly. You can then run with the confidence that you had in your previous run-time library.

Planning to link and run with Language Environment

Language Environment provides separate libraries for linking and running applications. The link libraries, of which SCEELKED is one, contain static (resident) routines that are linked with the application and used to resolve external references at link-edit time. The load library, of which SCEERUN is one, contains dynamic routines that are not part of the application and are dynamically loaded at run time. Language Environment callable services and other routines, such as those for initialization and termination, are located in SCEERUN. For a complete list of libraries and which phase of application development they are used in, see *z/OS Language Environment Customization*.

You will need to modify the job control statements in your input stream to point directly to SCEELKED and SCEERUN, or to point to the appropriate IBM-supplied cataloged procedures, if your job uses cataloged procedures. See *z/OS Language Environment Programming Guide* for more information about linking and running and using cataloged procedures.

On z/OS systems, you can install reentrant members of the SCEERUN data set in the link pack area (LPA) for faster retrieval. IBM provides a data set called SCEELPA and highly recommends putting this data set in the LPA (or LPALSTxx). This data set contains modules that are reentrant, reside above the line, and are heavily used by z/OS itself.

Chapter 2. Migrating from another Language Environment release

This topic provides information about migrating from one release of Language Environment to another. This topic explains upward compatibility as well as downward compatibility. Please look at any migration considerations listed in this topic for the release you are migrating to as well as any releases you are skipping over.

Language Environment provides general object and load module compatibility for applications that ran with a previous release of Language Environment. All Language Environment-enabled applications that have been linked with a minimum level of Language Environment for MVS and VM 1.3 will continue to run with later releases of Language Environment without the need to relink the application. If you experience any problems (for example, an application that worked with Language Environment for MVS and VM 1.3 no longer works after you install the current release of Language Environment), you should report them to IBM.

Most load modules are compatible with any level of Language Environment that is equivalent to, or higher than, the level used to link-edit them. Similarly, object modules can be link-edited with any level of Language Environment that is equivalent to, or higher than, the level required by the compiler that generated them.

Please see any exceptions in this topic.

Migration actions required for each release

This topic describes common activities and considerations that are typically required when you migrate from one release of Language Environment to another:

1. Update the CICS System Definition (CSD) file using the program definitions in the CEECCSD member (and CEECCSDX member for CICS TS 3.1) found in the SCEESAMP data set. Language Environment may have changed (added or deleted) load modules in this release.
2. Update the Language Environment load modules that were placed in the link pack area (LPA). Sample members found in the SCEESAMP data set, which can be used to move load modules into LPA, should be reviewed with every release migration. See the table "Language Environment sample IEALPAnn or PROGxx Members in CEE.SCEESAMP" for the list of sample members and their changed content in *z/OS Language Environment Customization*.
3. If any Language Environment user exits were used at the previous release and you plan to use them with the new release, they must be re-linked using the new release of Language Environment.
4. Updates to sample jobs related to run-time options might be required.

Changes are required to the CEEWDOPT and CEEWCOPT sample jobs that update installation-wide defaults (CICS and non-CICS) when new options are added, sub-options are added, or when options are deleted.

Recommendation: Do one of the following:

Migrating from another Language Environment release

- Take new copies of the CEEDOPT and CEECOPT members from CEE.SCEESAMP and modify them according to the procedures outlined in *z/OS Language Environment Customization*.
- Apply necessary changes to existing sample jobs after reviewing the summary of changes in *z/OS Language Environment Programming Reference* pertaining to run-time options.

Changes might be required to the CEEWROPT sample jobs that set region defaults for CICS and IMS/LRR environments. When options receiving new sub-options or when deleted options are specified in these sample jobs, changes are required.

Recommendation: Apply necessary changes to existing sample jobs after reviewing the summary of changes in *z/OS Language Environment Programming Reference* pertaining to run-time options. Specifically, look for options with new sub-options or deleted options.

Changes might be required to the CEEWUOPT sample jobs that set application defaults. Changes are necessary to existing sample jobs only if it is desired to use settings other than the defaults for those options where new sub-options have been added, or when deleted options are specified. Review the summary of changes in *z/OS Language Environment Programming Reference* pertaining to run-time options to determine if changes to these sample jobs are needed.

For the CEEWROPT and CEEWUOPT sample jobs, changes would only be necessary to the existing jobs if you run them again on the new release. Consider changing any or all sample jobs when option defaults are changed.

5. In z/OS V1R7, a new PARMLIB member, CEEPRMxx, was added for Language Environment. You can use it to specify Language Environment run-time options for the system. Operator commands are also provided to allow you to query and update the active run-time options for the system. This simplifies the management of Language Environment options, particularly in multisystem environments, and makes it possible to move Language Environment customization out of assembler language modules maintained using SMP/E usermods. However, specifying Language Environment options using CEEDOPT, CEECOPT and CELQDOPT modules continues to be supported. For more information, see *z/OS Language Environment Customization* or *z/OS Language Environment Programming Reference*.

Migration considerations for Language Environment in z/OS V1R12

Setting run-time options as overrideable or nonoverrideable

Description: Before z/OS V1R12, all run-time options specified in a CEEPRMxx parmlib member were overrideable by default. Beginning with z/OS V1R12, you can set run-time options as overrideable or nonoverrideable in the CEEPRMxx parmlib member or with a SETCEE command using the OVR or NONOVR attribute. The ability to specify an option as overrideable or nonoverrideable removes a barrier to using CEEPRMxx.

Element or feature:	Language Environment
When change was introduced:	z/OS V1R12.
Applies to migration from:	z/OS V1R11 and z/OS V1R10.
Timing:	Before the first IPL of z/OS V1R12.

Migrating from another Language Environment release

Is the migration action required?	No, but recommended so you can eliminate use of the assembler language USERMODs to specify installation-wide run-time options, and use parmlib member CEEPRMxx instead.
Target system hardware requirements:	None.
Target system software requirements:	None.
Other system (coexistence or fallback) requirements:	None.
Restrictions:	None.
System impacts:	None.
Related IBM Health Checker for z/OS check:	None.

Steps to take: Set run-time options as overrideable or nonoverrideable in the CEEPRMxx parmlib member or by issuing the SETCEE command using the OVR or NONOVR attribute.

Now that run-time options can be specified as overrideable or nonoverrideable in a CEEPRMxx parmlib member, and with a SETCEE command, you can eliminate the use of assembler language USERMODs to specify installation-wide run-time options.

Reference information:

- For more details about specifying a CEEPRMxx parmlib member, see *z/OS Language Environment Customization*.
- For the updated CEEPRM00 sample parmlib member, which includes every option specified as overrideable, see the CEE.SCEESAMP data set.

Changes to the Language Environment run-time options report when issuing D CEE

Description: Starting in z/OS V1R12, changes are made to the Language Environment run-time options report when a D CEE command is issued. Before z/OS V1R12, the Language Environment run-time options report displayed all suboptions, even if they were not explicitly set for any run-time option that was specified. Starting in z/OS V1R12, when a valid option is specified with a parmlib member or a SETCEE command, only the suboptions specified are displayed when a D CEE command is issued. A comma is displayed as a placeholder for those suboptions not specified.

Element or feature:	Language Environment
When change was introduced:	z/OS V1R12.
Applies to migration from:	z/OS V1R11 and z/OS V1R10.
Timing:	Before the first IPL of z/OS V1R12.
Is the migration action required?	Yes, if you have an application that reads the output of a D CEE command.
Target system hardware requirements:	None.
Target system software requirements:	None.
Other system (coexistence or fallback) requirements:	None.

Migrating from another Language Environment release

Restrictions:	None.
System impacts:	None.
Related IBM Health Checker for z/OS check:	None.

Steps to take:

Examine any programs that read the output of a D CEE command to ensure compatibility with the updated run-time options report. Commas are now displayed for any suboptions that are not explicitly specified in a parmlib member or with a SETCEE command.

For example, if the following SETCEE command is issued:

```
SETCEE CEEDOPT,ALL31,ANYHEAP(4K),FILETAG(,AUTOTAG)
```

a subsequent D CEE,CEEDOPT command displays the following:

```
CEE3745I 09.32.13 DISPLAY CEEDOPT
NO MEMBERS SPECIFIED
LAST WHERE SET                               OPTION
-----
SETCEE command                               ALL31()
SETCEE command                               ANYHEAP(4096,,)
SETCEE command                               FILETAG(,AUTOTAG)
```

Reference information: For more information, see *z/OS Language Environment Customization* and *z/OS MVS System Commands*.

Removal of conversion table source code

Description: Starting in z/OS V1R12, the C/C++ run-time library will no longer ship any ucmmap source code or genxlt source code for character conversions now being performed by Unicode Services.

Element or feature:	Language Environment
When change was introduced:	z/OS V1R12.
Applies to migration from:	z/OS V1R11 and z/OS V1R10.
Timing:	After the first IPL of z/OS V1R12.
Is the migration action required?	Yes, if you use the iconv() family of functions to test to a "known conversion result" and experience testcase failures. Also, if you use custom conversion tables replacing those listed in either ucmmap.lst or genxlt.lst.
Target system hardware requirements:	None.
Target system software requirements:	None.
Other system (coexistence or fallback) requirements:	None.
Restrictions:	None.
System impacts:	None.
Related IBM Health Checker for z/OS check:	None.

Steps to take:

Migrating from another Language Environment release

- If you use customized conversion tables, you should now generate custom Unicode Services conversion tables.
- If you use the iconv() family of functions testing to a "known conversion result" and experience test case failures, you need to update your expected results to the new conversion results.
- If you want to create custom conversion tables involving any of the CCSIDs related to the conversion table source no longer being shipped, you should now generate custom Unicode Services conversion tables instead of custom Language Environment conversion tables.

The *installation prefix*.SCEEUMAP data set will no longer be shipped.

The /usr/lib/nls/locale/ucmap HFS directory will no longer be shipped.

Note: The _ICONV_TECHNIQUE environment variable must be set to the same technique search order value used for the customized Unicode Services table in order for the iconv() family of functions to use the customized Unicode Services table. For example, if you want the iconv() family of functions to use a user-defined Unicode Services table with a technique search order of 2, the _ICONV_TECHNIQUE environment variable should be set to 2LMREC.

Reference information: For information on how to generate and use custom Unicode Services conversion tables, see *z/OS Unicode Services User's Guide and Reference*.

Changes to the CICS CLER run-time options report

Description: Starting with z/OS V1R12, the Language Environment run-time options report displayed from the CICS CLER transaction is changed. The report is modified to have a wider LAST WHERE SET column to accommodate longer values, such as "Installation Non-overrideable." In addition, the report heading OPTIONS is changed to OPTION to match the other run-time options reports.

Element or feature:	Language Environment.
When change was introduced:	z/OS V1R12.
Applies to migration from:	z/OS V1R11 and z/OS V1R10.
Timing:	After the first IPL of z/OS V1R12.
Is the migration action required?	Yes, if you have an application that reads the output of a CICS CLER transaction.
Target system hardware requirements:	None.
Target system software requirements:	None.
Other system (coexistence or fallback) requirements:	None.
Restrictions:	None.
System impacts:	None.
Related IBM Health Checker for z/OS check:	None.

Steps to take: Examine programs that read the output of a CICS CLER transaction to ensure compatibility with the updated CLER run-time options report. The LAST

Migrating from another Language Environment release

WHERE SET column is now wider and the OPTIONS heading is changed to OPTION. The following is a subset of the new report to show the formatting changes:

LAST WHERE SET	OPTION
Installation default	ABPERC(NONE)
Installation default	ABTERMENC(ABEND)
Installation default	NOAIXBLD

Reference information: For more information, see *z/OS Language Environment Programming Guide* and *z/OS Language Environment Debugging Guide*.

Migration considerations for Language Environment in z/OS V1R11

Changes to the HEAPCHK run-time option

The HEAPCHK runtime option now has 4 additional sub-options. Users who use the CEEDOPT, CEECOPT and CELQDOPT usermods to set their installation default run-time options must make a change. Users who use CEEPRMxx to set their system default run-time options rather than the user mods are unaffected.

Steps to take if you use the usermods:

1. Consider using the CEEPRMxx parmlib member.
2. Compare your existing source for the installation-wide run-time options CSECT, CEEDOPT (non-CICS environment), CEECOPT (CICS environment), or CELQDOPT (AMODE 64 environment) with the new samples in the hlq.SCEESAMP data set to determine whether you need to change your defaults. If changes are necessary, you must make them and apply the corresponding usermods.
3. Understand the new HEAPCHK run-time option sub-options and their default values.
4. Determine if the default values are acceptable for your installation and adjust if needed.

Reference information: For details about specifying the HEAPCHK run-time option, see *z/OS Language Environment Customization* or *z/OS Language Environment Programming Reference*

Changes to Binary and Decimal Floating-Point support in the CICS Environment

Certain Binary and Decimal Floating-Point Exceptions that were previously reported with a CEE3207S message are now reported with the following messages: CEE3216S, CEE3217S, CEE3218S, CEE3219S, CEE3220S, CEE3221S, CEE3222S, CEE3223S, CEE3224S, CEE3225S, CEE3226S, CEE3227S, CEE3228S, CEE3229S, CEE3231S, CEE3232S, or CEE3233S. These messages are the same ones uses in non-CICS environments for Floating-Point exceptions.

The floating-point control register (FPC), floating-point registers 1,3,5,7,8-15, access registers (ARs), and high registers (HRs) are now saved and restored when applications are resumed after program checks and ABENDs when CICS TS 4 or higher is used. Any changes to these registers made by user condition handlers or signal catchers may be ignored when the registers are restored and the application is resumed.

The sample USRHDLR program, CEEWUCHA, has been changed to check for the new floating program check conditions 3216-3229 and 3231-3233. Any customized versions of CEEWUCHA that are in use may need to be updated.

Migration considerations for Language Environment in z/OS V1R10

HEAPPOOLS Consideration:

HEAPPOOLS was ignored for AMODE64 applications in previous releases, when specified using `_CEE_RUNOPTS`, but is supported as of z/OS V1R10. In previous releases, when an AMODE64 application spawned an AMODE31 process, and the HEAPPOOLS run-time option was specified using `_CEE_RUNOPTS`, it would be ignored by the AMODE64 application, but would be propagated and accepted by the AMODE31 process. Additionally, when specified using `_CEE_RUNOPTS`, if an AMODE31 application spawned an AMODE64 process, the AMODE31 application would accept the HEAPPOOLS run-time option, but the AMODE64 process would ignore it.

The HEAPPOOLS run-time option is no longer ignored when specified from `_CEE_RUNOPTS` in AMODE 64 applications. Users who format the CEEOCB must now format the HEAPPOOLS run-time option for AMODE 64 environments.

This support is also available to the following releases:

- z/OS V1R7 with PK41618
- z/OS V1R8 with PK47298
- z/OS V1R9 with PK49427

Note: PK44554 adds storage report and heap pools trace support for the above releases.

Health Check - `check(ibmcee,cee_using_le_parmlib)`:

This check verifies the use of LE parmllib support. See *IBM Health Checker for z/OS: User's Guide* for more information.

Changes to CEEDOPT location:

The CSECT CEEDOPT run-time option is located in CEEPLPKA. If you do not manually link the run-time option you are not affected by this location change.

Note: If you use the `++USERMOD(CEEWD01)` to update the installation-wide run-time options, you are not affected by this location change.

Changes to data exceptions:

Data exceptions generated by the Compare and Trap family of instructions (such as CRT, CGRT, CGFRT, CIT, CGIT, CLRT, CLGRT, CLGFRT, CLFIT, and CLGIT) will be handled differently in V1R10. These data exceptions are now result in message CEE3234S instead of CEE3207S. Also, if the condition results in a POSIX signal, the signal that is generated is SIGFPE with a signal code (`si_code`) of FPE_CTDXC.

Changes to PL/I stream I/O behavior:

PL/I stream I/O behavior has been changed in some situations. See Chapter 5, "Other HLL migration considerations," on page 33 for more information.

Changes to Venezuela and Malta currency:

The currency in Venezuela has changed from bolivar to bolivar fuerte. The national currency symbol has changed from Bs to BSF and the international currency symbol has changed from VEB to VEF. C/C++ users who want to keep using the old currency symbols, the Bs or VEB (bolivar), must use `setlocale()` with a locale name of "Es_VEO" for the language-territory part, instead of "Es_VE". Users of the CEE3MCS and CEE3MC2 callable services can only access the new currency symbols.

Malta is adopting the euro currency. Users who want to keep using the old currency symbol must use the `@preeuro` locales.

Migration considerations for Language Environment in z/OS V1R9

CEEDUMP run-time option added

The CEEDUMP run-time option is used to specify options to control the processing of the Language Environment dump report known as CEEDUMP.

Among the possible installation-wide options that can be used to affect the Language Environment dumps are the following:

- Set the number of lines to be displayed on each page of the CEEDUMP report.
- Indicate the default SYSOUT class and form-name to use for all dynamically allocated CEEDUMPs.
- Set the default values for the FREE and SPIN JCL DD attributes to use for all dynamically allocated CEEDUMPs.

Steps to take:

1. Consider using the CEEPRMxx parmlib member.
2. Compare your existing source for the installation-wide run-time options CSECT, CEEDOPT (non-CICS environment), or CEECOPT (CICS environment) with the new samples in the hlq.SCEESAMP data set to determine whether you need to change your defaults. If changes are necessary, you must make them and apply the corresponding usermods.
3. Understand the new CEEDUMP run-time option and its default suboption values.
4. Determine if the default values are acceptable for your installation and adjust if needed.

Reference information: For details about specifying the CEEDUMP run-time option, see *z/OS Language Environment Customization* or *z/OS Language Environment Programming Reference*

Changes to Language Environment dump output, options reports and storage reports

Although none of these reports are programming interfaces, the following has changed:

- In the Language Environment dump output, the traceback now has multiple parts. New columns of data have been added and others have been re-arranged. Refer to the *z/OS Language Environment Debugging Guide* for examples of the new format.

Migrating from another Language Environment release

- In the storage report, the HeapPools Summary section has a new column called Element Size and the column called Cell Size is now called Specified Cell Size. Refer to the *z/OS Language Environment Debugging Guide* for examples of the new format.
- Language Environment dump output, options reports and storage reports are now sensitive to the national language. When the national language is uppercase U.S. English or Japanese, titles, heading and keywords that were in mixed case U.S. English will now be in upper case U.S. English.

Changes to CELQPIPI

Any existing AMODE 64 PIPI application that currently specifies a non-zero value in the reserved third parameter of the CELQPIPI INIT_MAIN or INIT_SUB function must specify 0 in this 3rd parameter or it must point to an AMODE 64 PIPI service routine vector.

For more information, refer to the *z/OS Language Environment Programming Guide for 64-bit Virtual Addressing Mode*.

Changes to the CLER transaction

The CLER (CICS transaction) panel has changed as follows:

- The order of options on the CLER panel has changed to show them alphabetically.
- CHECK and INFOMSGFILTER have been added to the list of options.
- CLER users will now be prompted for confirmation if you use:
 - The ON suboption of CBLPSHPOP, RPTSTG and RTPOPT
 - The OFF suboption of ALL31

There are no actions you need to take.

Changes to XPLINK under LRR

z/OS V1.9 Language Environment now supports running XPLINK applications in an LRR (Library Routine Retention) environment. The new support requires the user to indicate if the LRR environment can support XPLINK applications. The default behavior when setting up an LRR environment is that it does not support XPLINK applications. If an attempt is made to run an XPLINK application in an LRR environment that does not support XPLINK, an ABEND will result.

There are two minor migration issues associated with this new support:

- Prior to z/OS V1.9, when a non-XPLINK main with XPLINK(ON) run-time option was run in an LRR environment, Language Environment forced the XPLINK run-time option to OFF and allowed the application to continue. For z/OS V1.9, this same application, when run in an LRR environment that does not support XPLINK, causes Language Environment to issue ABEND U4093 with reason code 178 (X'B2').
- Prior to z/OS V1.9, when an XPLINK main was run in an LRR environment, Language Environment issued ABEND U4093 with reason code 176 (X'B0'). For z/OS V1.9, this same application, when run in an LRR environment that does not support XPLINK, causes Language Environment to issue ABEND U4093 with reason code 177 (X'B1').

Heap Pools Consideration:

HEAPPOOLS and HEAPPOOLS64 changes

Migrating from another Language Environment release

The storage required for HEAPPOOLS control structures has increased by approximately 3k.

The storage required for HEAPPOOLS64 control structures has increased by approximately 3k.

Note: This change does not affect user heap pools created with the `__ucreate()` function.

Changes to messages

- The following messages have been added to Language Environment for this release as part of the support for IEEE Decimal Floating Point (DFP) for C/C++ programs:
 - EDC6259S
 - CEE3226S
 - CEE3227S
 - CEE3228S
 - CEE3229S
 - CEE3231S
 - CEE3232S
 - CEE3233S
- The following messages have been updated for this release as part of the DLL enhancements for C/C++ programs:
 - EDC5204E
 - EDC5205S
 - EDC5206S
 - EDC5207S
 - EDC5208I
 - EDC5209I
 - EDC5210I
 - EDC5212I
 - EDC5213I
 - EDC5214I
 - EDC5215I
 - EDC5216I
 - EDC5217I
 - EDC5218I
 - EDC5220I
 - EDC5221S
 - EDC5225E
 - EDC5226S
 - EDC5234S
 - EDC5237S
 - EDC5251I
 - EDC5252S
 - EDC5253S
 - EDC5254S

Chapter 3. Migrating from other run-time environments

This topic describes, in general, the compatibility of Language Environment with previous run-time libraries. It also describes what you must do to migrate different object and load modules to Language Environment.

Note: This publication does not describe all migration considerations. For a detailed description of migration considerations, see the appropriate language migration guide listed in the following topic.

Compatibility with previous run-time libraries

With certain exceptions, Language Environment provides object and load module compatibility for applications that are generated with the following pre-Language Environment IBM language products. Load modules that are created with these compilers and link-edited with their associated run-time libraries run compatibly with Language Environment without relinking. Also, object modules created with these compilers can be linked and run with Language Environment without recompiling.

- C/370 Versions 1 and 2
- OS/VS COBOL Release 2
- VS COBOL II Release 3 or later
- OS PL/I Version 1 Release 3 (object modules), Version 1 Release 5.1 and Version 2, all releases (load modules)
- VS FORTRAN Versions 1 and 2 (MVS only)
- FORTRAN IV H Extended (MVS only)
- FORTRAN IV G1 (MVS only)

The following topics contain some basic information to help you determine if your applications will run compatibly with Language Environment. For more detailed information about compatibility, see one of the following migration guides:

- *z/OS XL C/C++ Compiler and Run-Time Migration Guide for the Application Programmer*
- *IBM C for VM/ESA Compiler and Run-Time Migration Guide*
- *Enterprise COBOL for z/OS, V4R2, Compiler and Runtime Migration Guide, GC23-8527, or Enterprise COBOL for z/OS, V3R4, Compiler and Runtime Migration Guide, GC27-1409.*
- *VisualAge PL/I for OS/390 Compiler and Run-Time Migration Guide*
- *PL/I for MVS & VM Compiler and Run-Time Migration Guide or Enterprise PL/I for z/OS, V3R9, Migration Guide*
- *Fortran Run-Time Migration Guide*

Migrating ILC applications to Language Environment

Table 2 lists some of the compatibility exceptions you should consider when migrating ILC applications to Language Environment.

Table 2. ILC Compatibility Exceptions

To Migrate:	You Need To:
Load modules that contain OS/VS COBOL, with calls to, or from, OS PL/I	Upgrade the COBOL source code and compile with Enterprise COBOL for z/OS or COBOL for OS/390 & VM.
Load modules that contain VS COBOL II Version 1 Release 3 or later, with calls to, or from, OS PL/I	Relink with Language Environment. However, if you link your VS COBOL II-OS PL/I ILC applications with the migration tool provided by OS PL/I Version 2 Release 3, you will not need to relink your applications. The PTF numbers for the migration aid are UN76954 and UN76955. For information about the migration tool, see <i>Enterprise PL/I for z/OS, V3R9, Migration Guide</i> or <i>PL/I for MVS & VM Compiler and Run-Time Migration Guide</i> .
C/370 Version 2 Release 2 (V2R2) load modules that contain calls to, or from, VS COBOL II, COBOL/370, or COBOL for MVS & VM programs	Apply the PTF associated with APAR PN74931, which allows you to relink C/370 V2R2 load modules with the C/370 V2R2 library and run with Language Environment or the C/370 V2R2 library.
Load modules that contain Fortran with calls to, or from, any other language	Relink the load modules with z/OS Language Environment, using the Language Environment libraries rather than pre-Language Environment Fortran libraries. Fortran and PL/I provide migration tools. For information about the Fortran library replacement tool, see <i>z/OS Language Environment Programming Guide</i> ; for information about the PL/I migration tool, see <i>Enterprise PL/I for z/OS, V3R9, Migration Guide</i> or <i>PL/I for MVS & VM Compiler and Run-Time Migration Guide</i> .

See *z/OS XL C/C++ Compiler and Run-Time Migration Guide for the Application Programmer*, or *IBM C for VM/ESA Compiler and Run-Time Migration Guide* for detailed instructions on how to relink C-COBOL ILC applications. (You do not need to relink PL/I-C ILC applications.)

See *Enterprise PL/I for z/OS, V3R9, Migration Guide*, *PL/I for MVS & VM Compiler and Run-Time Migration Guide* or *VisualAge PL/I for OS/390 Compiler and Run-Time Migration Guide* for instructions on how to relink PL/I-COBOL ILC applications, and for information about a migration aid that helps migrate OS PL/I-VS COBOL II ILC applications.

For more information about relinking C-Fortran ILC applications, see *z/OS Language Environment Programming Guide* or *z/OS XL C/C++ Compiler and Run-Time Migration Guide for the Application Programmer*.

Migrating C routines to Language Environment

Generally, you can directly migrate most C/370 Version 1 or Version 2 applications to any release of Language Environment. However, you must use the Language Environment libraries to relink an application if a load module contains one of the following items:

- ILC calls to, and from, Fortran or in some cases COBOL (see Table 2 on page 16)
- Debugging information (that is, they are compiled with the TEST option)
- System Programming C Facility (SPC) load modules that contain dynamic C/370 library functions

For detailed information about migrating your C applications, see *z/OS XL C/C++ Compiler and Run-Time Migration Guide for the Application Programmer*.

Migrating COBOL programs to Language Environment

Table 3 contains a subset of COBOL compatibility exceptions.

Table 3. COBOL Compatibility Exceptions

To Migrate:	You Need To:
OS/VS COBOL programs mixed with assembler under non-CICS	Run in a single run unit (SVC LINK is not allowed).
OS/VS COBOL programs that use ILC with PL/I	Upgrade the COBOL source code to Enterprise COBOL for z/OS or COBOL for OS/390 & VM.
OS/VS COBOL programs that use ILC with FORTRAN	Upgrade the COBOL source code to Enterprise COBOL for z/OS or COBOL for OS/390 & VM.
VS COBOL II programs that use ILC with C or PL/I	See Table 2 on page 16 for information about migration aids for each language.

Recommendation: You should not install more than one library for a language in the LNKLST or LPALST. You should not concatenate pre-Language Environment run-time libraries in the LNKLST.

See *Enterprise COBOL for z/OS, V4R2, Compiler and Runtime Migration Guide, GC23-8527* and *Enterprise COBOL for z/OS, V3R4, Compiler and Runtime Migration Guide, GC27-1409* for detailed migration information about LNKLST concatenation and COBOL.

Migrating Fortran routines to Language Environment

Table 4 lists some compatibility exceptions to consider when migrating Fortran applications to Language Environment. For more information, see *Fortran Run-Time Migration Guide*.

Table 4. Fortran Compatibility Exceptions

To Migrate:	You Need To:
Object modules compiled with VS FORTRAN programs or subprograms that receive character arguments or pass character arguments to subprograms	Recompile with VS FORTRAN Version 2 and Version 1 Release 2.0 or earlier and are either run under Language Environment.

Migrating other run-time environments

Table 4. Fortran Compatibility Exceptions (continued)

To Migrate:	You Need To:
Object modules compiled with VS FORTRAN Version 2 Release 5 or 6 that contain parallel constructs, use the PARALLEL compile-time option, or invoke PEORIG, PEPOST, PEWAIT, PETERM, PLCOND, PLFREE, PLLOCK, PLORIG, or PLTERM	Continue to link-edit and run under VS FORTRAN Version 2. These object modules cannot run under Language Environment.
Object modules compiled with VS FORTRAN Version 2 Release 5 or 6 using the EC compiler option	Perform one of the following actions, as these object modules cannot run under Language Environment: <ul style="list-style-type: none"> • Continue to link-edit and run under VS FORTRAN Version 2 Release 5 or 6, or • Remove the EC option from your source, if possible, then recompile and run with Language Environment.
Object modules with calls to DVCHK or OVERFL services	Remove the calls, change the logic of the program and recompile with VS FORTRAN Version 2.
Object modules that have dependences on product internals	Remove the dependencies, change the logic of the program and recompile with VS FORTRAN Version 2.
Object modules that have misaligned vector operands	Ensure that all vector operands are properly aligned and recompile with VS FORTRAN Version 2.
Object modules that use static debug	Remove the debug packets and recompile with VS FORTRAN Version 2.
Load modules that contain Fortran with calls to, or from, any other language	See Table 2 on page 16 for instructions.

Migrating PL/I routines to Language Environment

Table 5 lists some compatibility exceptions for migrating PL/I routines to Language Environment. See *VisualAge PL/I for OS/390 Compiler and Run-Time Migration Guide*, *Enterprise PL/I for z/OS, V3R9, Migration Guide* or *PL/I for MVS & VM Compiler and Run-Time Migration Guide* for more information.

Table 5. PL/I Compatibility Exceptions

To Migrate:	You Need To:
Object modules created with OS PL/I Version 1 Release 1 through Version 1 Release 2.3 compilers	Recompile with Enterprise PL/I, PL/I for MVS & VM or with the OS PL/I Version 2 compiler.
Load modules created with OS PL/I Version 1 Releases 3 through 5.	Relink with Language Environment or with OS PL/I Version 2.
Load modules created with OS PL/I Version 1 Release 5.1.	Apply the IBM-supplied program fix (ZAP) before running the following types of OS PL/I V1 R5.1 load modules: <ul style="list-style-type: none"> • Main load modules for MVS non-shared library, non-CICS, nonmultitasking

Table 5. PL/I Compatibility Exceptions (continued)

To Migrate:	You Need To:
Load modules that use the OS PL/I shared library	<p>Relink or recompile load modules from OS PL/I Version 1 Releases 1 through 5 shared library; these load modules are not supported.</p> <p>Load modules from OS PL/I Version 1 Release 5.1 and the Version 2 shared library are supported; however, you must rebuild the shared library once under Language Environment.</p>

Migrating assembler programs to Language Environment

To run assembler programs with Language Environment, you must ensure the assembler programs adhere to conventions for items such as register and storage usage, condition handling, and accessing input parameters. For example, assembler programs must set a valid 31 bit address in the save area back chain.

Language Environment provides several assembler macros, which your assembler programs should use to perform tasks such as entering and exiting assembler routines and mapping Language Environment data areas. For example, when you use the CEEENTRY and CEETERM macros, Language Environment automatically initializes and terminates, respectively, the execution environment for the application. In addition, when the Language Environment environment is established for the main assembler program, that environment is also established for any other routines that may be called later.

For more information about assembler considerations and Language Environment macros, see *z/OS Language Environment Programming Guide*. For more information about assembler considerations when assembler programs are used with COBOL, see *Enterprise COBOL for z/OS, V4R2, Compiler and Runtime Migration Guide*, GC23-8527, or *Enterprise COBOL for z/OS, V3R4, Compiler and Runtime Migration Guide*, GC27-1409.

Chapter 4. Choosing run-time options for compatible behavior

This topic provides information on how Language Environment run-time options differ from run-time options that are specific to a high-level language (HLL). It also provides the Language Environment default settings and the recommended settings for C, COBOL, and PL/I applications running in CICS and non-CICS environments. Fortran does not run in the CICS environment.

Differences between run-time options

Language Environment provides a set of run-time options for applications. These options are processed at the enclave level and allow you to control many aspects of the Language Environment environment. The options comparison tables show how Language Environment run-time options differ from the run-time options that are specific to C, COBOL, Fortran, and PL/I (if an HLL run-time option is not listed in a table, you can assume it operates under Language Environment in the same way it did before Language Environment):

High-Level Language	Language Environment Option Information
C	Table 6
COBOL	Table 7 on page 22
Fortran	Table 8 on page 24
PL/I	Table 9 on page 25

C and Language Environment run-time options comparison

Table 6. C and Language Environment Run-Time Options

C Option	Language Environment Equivalent	Notes
ISAINC	STACK	If you do not change the C/370 run-time option ISAINC, you will receive a warning message during execution.
ISASIZE	STACK	If you do not change the C/370 run-time option ISASIZE, you will receive a warning message during execution.
LANGUAGE	NATLANG	Mixed-case and uppercase US English and Japanese are supported. If you do not change the C/370 run-time option LANGUAGE, you will receive a warning message during execution.
REPORT NOREPORT	RPTSTG(ON OFF), RPTOPT(ON OFF)	RPTSTG(ON OFF) and RPTOPT(ON OFF) provide behavior compatible with REPORT NOREPORT, and affect all languages in an enclave. If you do not change the C/370 run-time option REPORT NOREPORT, you will receive a warning message during execution.
SPIE NOSPIE STAE NOSTAE	TRAP(ON,SPIE) TRAP(OFF)	If either SPIE or STAE is specified or defaulted in input, TRAP is set to TRAP(ON,SPIE). If both NOSPIE and NOSTAE are specified, TRAP is set to TRAP(OFF). TRAP(ON,SPIE) is the recommended setting.

Choosing compatible run-time options

COBOL and Language Environment run-time options comparison

Table 7. COBOL and Language Environment Run-Time Options

COBOL Option	Language Environment Equivalent	Notes
AIXBLD NOAIXBLD	AIXBLD NOAIXBLD	<p>Invokes the access methods services for VSAM indexed and relative data sets to complete the file and index definition procedures for COBOL routines.</p> <p>Under z/OS, Access Method Services (AMS) messages are directed to the ddname specified in the Language Environment run-time option MSGFILE. Under CMS, the messages are erased, which is the same behavior as VS COBOL II.</p> <p>AIXBLD NOAIXBLD is not applicable under CICS.</p>
DEBUG NODEBUG	DEBUG NODEBUG	DEBUG NODEBUG provides behavior compatible with VS COBOL II.
FLOW NOFLOW	FLOW NOFLOW	FLOW NOFLOW provides behavior compatible with VS COBOL II.
LANGUAGE	NATLANG	NATLANG replaces LANGUAGE, which is a VS COBOL II installation option. You can select a national language at run time or installation time by using the NATLANG option.
LIBKEEP NOLIBKEEP	Not applicable	<p>LIBKEEP NOLIBKEEP is not supported under Language Environment and is not applicable under CICS.</p> <p>To obtain similar function, use the Library Routine Retention (LRR) feature, which is described in <i>z/OS Language Environment Programming Guide</i>. To use LRR in an IMS/TM environment, see <i>z/OS Language Environment Customization</i>.</p>
MIXRES NOMIXRES	Not applicable	<p>MIXRES NOMIXRES is not supported under Language Environment and is not applicable under CICS.</p> <p>Mixed RES and NORES applications when linked with Language Environment will exhibit RES-like behavior; see <i>Enterprise COBOL for z/OS, V4R2, Compiler and Runtime Migration Guide, GC23-8527</i>, or <i>Enterprise COBOL for z/OS, V3R4, Compiler and Runtime Migration Guide, GC27-1409</i> for more information.</p>
QUEUE	Not applicable	QUEUE is not supported under Language Environment.

Table 7. COBOL and Language Environment Run-Time Options (continued)

COBOL Option	Language Environment Equivalent	Notes
RTEREUS NORTEREUS	RTEREUS NORTEREUS	<p>RTEREUS is not recommended as an installation default. Use RTEREUS only for specific applications and ensure that you understand the possible side effects, for example:</p> <ul style="list-style-type: none"> • Under Language Environment, RTEREUS(ON) is only supported in a single enclave environment. Applications that create multiple enclaves will terminate with error message IGZ0168S. Multiple enclaves can be created by applications that use SVC LINK or CMSCALL to invoke application programs. One example is when an SVC LINK is used to invoke an application program under ISPF that is using ISPF services (such as CALL 'ISPLINK' and ISPF SELECT). • If a Language Environment reusable environment is established (using RTEREUS), attempts to run a C or PL/I main program under Language Environment will fail. For example, when running on ISPF with RTEREUS(ON): <ul style="list-style-type: none"> – The first program invoked by ISPF is a COBOL program; a Language Environment reusable environment is established. – At another point, ISPF invokes a PL/I or C program; the initialization of the PL/I or C program will fail. • If many COBOL programs are run under the same z/OS task, “out of storage” abends may occur. This occurs because all storage acquired by Language Environment to run COBOL programs is kept until the z/OS task ends or the Language Environment environment terminates. • Language Environment does not produce storage and run-time options reports unless STOP RUN is issued to end the enclave.
SIMVRD NOSIMVRD	SIMVRD NOSIMVRD	SIMVRD NOSIMVRD provides behavior compatible with the VS COBOL II SIMVRD NOSIMVRD option.
SPOUT NOSPOUT	RPTOPTS(ON OFF), RPTSTG(ON OFF)	Storage reports are directed to the ddname specified in the Language Environment option MSGFILE. For more information, see <i>Enterprise COBOL for z/OS, V4R2, Compiler and Runtime Migration Guide</i> , GC23-8527, or <i>Enterprise COBOL for z/OS, V3R4, Compiler and Runtime Migration Guide</i> , GC27-1409.
SSRANGE NOSSRANGE	CHECK(ON OFF)	CHECK(ON OFF) provides behavior compatible with SSRANGE NOSSRANGE.
STAE NOSTAE	TRAP(ON,SPIE) TRAP(OFF)	If STAE NOSTAE is specified in input, then TRAP is set according to the option: TRAP(ON,SPIE) for STAE, and TRAP(OFF) for NOSTAE. TRAP(ON,SPIE) is the recommended setting.
UPSI	UPSI	UPSI provides behavior compatible with the VS COBOL II UPSI option.
WSCLEAR NOWSCLEAR	STORAGE(00,,)	For behavior similar to WSCLEAR NOWSCLEAR, use the Language Environment STORAGE(00,,) option. For more information, see <i>Enterprise COBOL for z/OS, V4R2, Compiler and Runtime Migration Guide</i> , GC23-8527, or <i>Enterprise COBOL for z/OS, V3R4, Compiler and Runtime Migration Guide</i> , GC27-1409.

Choosing compatible run-time options

Fortran and Language Environment run-time options comparison

Table 8. Fortran and Language Environment Run-Time Options

Fortran Option	Language Environment Equivalent	Notes
ABSDUMP NOABSDUMP	TERMTHDACT	TERMTHDACT(DUMP) replaces ABSDUMP to produce a Language Environment dump at termination, but there is no automatic mapping. TERMTHDACT with suboptions TRACE, QUIET, MSG, UATRACE, UAONLY, or UAIMM replaces NOABSDUMP to avoid getting a Language Environment dump at termination.
AUTOTASK NOAUTOTASK	AUTOTASK NOAUTOTASK	AUTOTASK NOAUTOTASK provides behavior compatible with VS FORTRAN Version 2.
CNVIOERR NOCNVIOERR	Not applicable	There is no Language Environment equivalent for CNVIOERR NOCNVIOERR. Fortran semantics are as though CNVIOERR were in effect.
DEBUG NODEBUG	Not applicable	There is no debugger support for Fortran.
DEBUNIT	Not applicable	There is no Language Environment equivalent for DEBUNIT.
ECPACK NOECPACK	Not applicable	There is no Language Environment equivalent for ECPACK NOECPACK. You cannot run programs with Language Environment that use access registers or that were compiled with the EC or EMODE compiler options.
ERRUNIT	ERRUNIT	ERRUNIT provides behavior compatible with VS FORTRAN Version 2.
FAIL	ABTERMENC	ABTERMENC replaces FAIL, but there is no automatic mapping. ABTERMENC controls whether a condition of severity 2 or greater is terminated with a return code or an abend. ABTERMENC(RETCODE) is similar to FAIL(RC), and ABTERMENC(ABEND) is similar to FAIL(ABEND).
FILEHIST NOFILEHIST	FILEHIST NOFILEHIST	FILEHIST NOFILEHIST provides behavior compatible with VS FORTRAN Version 2.
INQPCOPN NOINQPCOPN	INQPCOPN NOINQPCOPN	INQPCOPN NOINQPCOPN provides behavior compatible with VS FORTRAN Version 2.
IOINIT NOIOINIT	Not applicable	There is no Language Environment equivalent for IOINIT NOIOINIT. The message file is opened either when the first record is written to it or when an OPEN statement refers to error message unit. If no allocation for the ddname has been made for the message file, it is dynamically allocated to the terminal (under TSO) or to SYSOUT=* (under z/OS batch).

Table 8. Fortran and Language Environment Run-Time Options (continued)

Fortran Option	Language Environment Equivalent	Notes
OCSTATUS NOOCSTATUS	OCSTATUS NOOCSTATUS	OCSTATUS NOOCSTATUS provides behavior compatible with VS FORTRAN Version 2.
PARALLEL NOPARALLEL	Not applicable	There is no Language Environment equivalent for PARALLEL NOPARALLEL. Parallel programs cannot be run with Language Environment.
PC NOPC	PC NOPC	PC specifies that Fortran static common blocks with the same name but in different load modules do not refer to the same storage.
PRTUNIT	PRTUNIT	PRTUNIT provides behavior compatible with VS FORTRAN Version 2.
PTRACE NOPTRACE	Not applicable	There is no Language Environment equivalent for PTRACE NOPTRACE. Parallel programs cannot be run with Language Environment.
PUNUNIT	PUNUNIT	PUNUNIT provides behavior compatible with VS FORTRAN Version 2.
RDRUNIT	RDRUNIT	RDRUNIT provides behavior compatible with VS FORTRAN Version 2.
RECPAD NORECPAD	RECPAD(OFF NONE VAR ALL ON)	NORECPAD automatically maps to RECPAD(OFF). Fortran does not support RECPAD(VAR). RECPAD must be changed to RECPAD(ON).
SPIE NOSPIE STAE NOSTAE	TRAP(ON,SPIE) TRAP(OFF)	If either SPIE or STAE is specified or defaulted in input, TRAP is set to TRAP(ON,SPIE). If both NOSPIE and NOSTAE are specified, TRAP is set to TRAP(OFF). TRAP(ON,SPIE) is the recommended setting.
XUFLOW NOXUFLOW	XUFLOW(ON AUTO) XUFLOW(OFF)	There is no automatic mapping of XUFLOW to the Language Environment XUFLOW. NOXUFLOW maps to the Language Environment XUFLOW(OFF), which provides compatible behavior.

PL/I and Language Environment run-time options comparison

Table 9. PL/I and Language Environment Run-Time Options

PL/I Option	Language Environment Equivalent	Notes
COUNT NOCOUNT	Not applicable	There is no Language Environment equivalent for COUNT NOCOUNT. It is not processed but produces an informational message.

Choosing compatible run-time options

Table 9. PL/I and Language Environment Run-Time Options (continued)

PL/I Option	Language Environment Equivalent	Notes
FLOW NOFLOW	Not applicable	There is no Language Environment equivalent for FLOW NOFLOW. Language Environment honors this option only as a COBOL option.
ISAINC	STACK, THREADSTACK, or PLITASKCOUNT	ISAINC maps to three Language Environment options, STACK, NONIPTSTACK, and PLITASKCOUNT, which provide compatible behavior.
ISASIZE	STACK, THREADSTACK, or PLITASKCOUNT	ISASIZE maps to three Language Environment options, STACK, NONIPTSTACK, and PLITASKCOUNT, which provide compatible behavior.
LANGUAGE	NATLANG	Mixed-case and uppercase U.S. English and Japanese are supported.
REPORT NOREPORT	RPTSTG(ON OFF) RPTOPTS(ON OFF)	RPTSTG(ON OFF) and RPTOPTS(ON OFF) provide behavior compatible with REPORT NOREPORT.
SPIE NOSPIE STAE NOSTAE	TRAP(ON,SPIE) TRAP(OFF)	If either SPIE or STAE is specified or defaulted in input, TRAP is set to TRAP(ON,SPIE). If both NOSPIE and NOSTAE are specified, TRAP is set to TRAP(OFF). TRAP(ON,SPIE) is the recommended setting.
TASKHEAP	THREADHEAP	THREADHEAP provides behavior compatible with TASKHEAP.

Run-time option summary and recommendations

Table 10 summarizes the Language Environment run-time options, defaults, and recommended settings for applications running in CICS and non-CICS (for example, batch or IMS) environments. For more information about how to use these options, including the full syntax and additional usage notes, see *z/OS Language Environment Programming Reference*. *z/OS Language Environment Programming Guide* contains additional compatibility information about these options.

Some options apply to all high-level languages; others are only applicable to specific languages. These options are identified by table notes, which are described in 29. The recommended setting for some run-time options can vary, depending upon the language used to create the application or if multiple (Multi) languages are used in the environment. When a recommendation varies, the applicable settings for the languages are listed in the table. Also, the table identifies the run-time options that are not applicable (N/A) in either the CICS or non-CICS environment; Language Environment ignores these options if they are specified.

Table 10. Language Environment Run-Time Options, Defaults, and Recommendations

Option	Non-CICS		CICS		Notes
	Default	Recommended	Default	Recommended	
ABPERC	NONE	NONE	N/A	N/A	1
ABTERMENC	ABEND	ABEND	ABEND	ABEND	1, 2

Run-time option summary

Table 10. Language Environment Run-Time Options, Defaults, and Recommendations (continued)

Option	Non-CICS		CICS		Notes
	Default	Recommended	Default	Recommended	
AIXBLD NOAIXBLD	NOAIXBLD	NOAIXBLD	N/A	N/A	3
ALL31	ON	ON	ON	ON	1, 4
ANYHEAP	16K,8K,ANY,FREE	16K,8K,ANY,FREE (C, COBOL, Multi, PL/I) 48K,8K,ANY,FREE (Fortran)	4K,4080,ANY,FREE	4K,4080,ANY,FREE	1, 5, 29
ARGPARSE	ARGPARSE	ARGPARSE	N/A	N/A	12, 7
AUTOTASK	NOAUTOTASK	NOAUTOTASK	N/A	N/A	8
BELOWHEAP	8K,4K,FREE	8K,4K,FREE	4K,4080,FREE	4K,4080,FREE	1, 29
CBLOPTS	ON	ON	N/A	N/A	3, 9
CBLPSHPOP	ON	N/A	ON	ON	3
CBLQDA	OFF	OFF	N/A	N/A	3
CEEDUMP	60, SYSOUT=*, FREE=END, SPIN=UNALLOC	60, SYSOUT=*, FREE=END, SPIN=UNALLOC	60, SYSOUT=*, FREE=END, SPIN=UNALLOC	60, SYSOUT=*, FREE=END, SPIN=UNALLOC	1
CHECK	ON	ON	ON	ON	3
COUNTRY	US	User-defined	US	User-defined	1, 10
DEBUG	DEBUG(OFF)	DEBUG(OFF)	DEBUG(OFF)	DEBUG(OFF)	3, 11
DEPTHCONDLMT	10	0	10	0	1
DYNDUMP	*USERID, NODYNAMIC, TDUMP	*USERID, NODYNAMIC, TDUMP	*USERID, NODYNAMIC, TDUMP	*USERID, NODYNAMIC, TDUMP	1
ENV	No default	User-defined	No default	User-defined	7, 12
ENVAR	"	"	"	"	1
ERRCOUNT	0	0	0	0	1
ERRUNIT	6	6	N/A	N/A	8
EXECOPS	EXECOPS	EXECOPS	N/A	N/A	7, 12
FILEHIST	FILEHIST	FILEHIST	N/A	N/A	8
FILETAG	NOAUTOCVT, NOAUTOTAG	NOAUTOCVT, NOAUTOTAG	N/A	N/A	12
FLOW	NOFLOW	FLOW	N/A	N/A	3, 7
HEAP	32K,32K,ANY, KEEP,8K,4K	32K,32K,ANY, KEEP,8K,4K (C, COBOL, Multi, PL/I) 4K,4K,ANY,KEEP, 8K,4K (Fortran)	4K,4080,ANY, KEEP,4K,4080	4K,4080,ANY, KEEP,4K,4080	1, 5, 29
HEAP64	1M,1M,KEEP,32K,32K, KEEP,4K,4K,FREE	N/A	N/A	N/A	30
HEAPCHK	OFF,1,0,0,0, 1024,0,1024,0	OFF,1,0,0,0, 1024,0,1024,0	OFF,1,0,0,0, 1024,0,1024,0	OFF,1,0,0,0, 1024,0,1024,0	1
HEAPOOLS	OFF,8,10,32,10, 128,10,256,10, 1024,10,2048,10	User-defined	OFF,8,10,32,10, 128,10,256,10, 1024,10,2048,10	User-defined	13, 14

Run-time option summary

Table 10. Language Environment Run-Time Options, Defaults, and Recommendations (continued)

Option	Non-CICS		CICS		Notes
	Default	Recommended	Default	Recommended	
HEAPOOLS64	OFF,8,4000,32,2000, 128,700,256,350, 1024,100,2048,50, 3072,50,4096,50, 8192,25,16384,10, 32768,5,65536,5	N/A	N/A	N/A	30
INFOMSGFILTER	OFF	OFF	OFF	OFF	1
INQPCOPN	INQPCOPN	INQPCOPN	N/A	N/A	8
INTERRUPT	OFF	OFF	N/A	N/A	1
IOHEAP64	1M,1M,FREE,12K,8K, FREE,4K,4K,FREE	N/A	N/A	N/A	30
LIBHEAP64	1M,1M,FREE,16K,8K, FREE,8K,4K,FREE	N/A	N/A	N/A	30
LIBSTACK	4K,4K,FREE	4K,4K,FREE	32,4080,FREE	32,4080,FREE	1
MSGFILE	SYSOUT,FBA,121,0, NOENQ	<i>ddname</i>	N/A	N/A	1, 16
MSGQ	15	15	N/A	N/A	1
NATLANG	ENU	ENU	ENU	ENU	1
OCSTATUS	OCSTATUS	OCSTATUS	N/A	N/A	8
PC	NOPC	NOPC	N/A	N/A	8
PLIST	HOST	HOST	N/A	N/A	7, 12
PLITASKCOUNT	20	20	N/A	N/A	18
POSIX	OFF	OFF	N/A	N/A	1
PROFILE	OFF,"	OFF,"	OFF,"	OFF,"	12, 19
PRTUNIT	6	6	N/A	N/A	8
PUNUNIT	7	7	N/A	N/A	8
RDRUNIT	5	5	N/A	N/A	8
RECPAD	RECPAD(OFF)	RECPAD(OFF)	N/A	N/A	8
REDIR	REDIR	REDIR	N/A	N/A	7, 12
RPTOPTS	OFF	OFF	OFF	OFF	1
RPTSTG	OFF	OFF	OFF	OFF	1
RTEREUS	RTEREUS(OFF)	RTEREUS(OFF)	N/A	N/A	3
SIMVRD	SIMVRD(OFF)	SIMVRD(OFF)	N/A	N/A	3
STACK	128K,128K,ANY, KEEP, 512K,128K	128K,128K,ANY,KEEP, 512K,128K (C, Fortran, Multi, PL/I) 64K,64K,ANY,KEEP (COBOL)	4K,4080,ANY,KEEP, 4K,4080	4K,4080,ANY,KEEP, 4K,4080	1, 20, 23, 29
STACK64	1M,1M,128M	N/A	N/A	N/A	30
STORAGE	NONE,NONE, NONE,0K	NONE,NONE, NONE,0K	NONE,NONE, NONE,0K	NONE,NONE, NONE,0K	1, 22, 24, 31
TERMTHDACT	TRACE,,96	TRACE,,96 (C, Fortran, Multi, PL/I) UATRACE,,96 (COBOL)	TRACE,CESE,96	TRACE,CICSDDS,96 (C, Fortran, Multi, PL/I) UATRACE,CIDSDDS, 96 (COBOL)	1, 15, 21

Table 10. Language Environment Run-Time Options, Defaults, and Recommendations (continued)

Option	Non-CICS		CICS		Notes
	Default	Recommended	Default	Recommended	
TEST	NOTEST (ALL,*, PROMPT, INSPREF)	NOTEST (ALL,*, PROMPT, INSPREF)	NOTEST (ALL,*, PROMPT, INSPREF)	NOTEST (ALL,*, PROMPT, INSPREF)	1
THREADHEAP	4K,4K,ANY,KEEP	4K,4K,ANY,KEEP	N/A	N/A	1
THREADSTACK	OFF,4K,4K,ANY,KEEP, 128K,128K	OFF,4K,4K,ANY,KEEP, 128K,128K	N/A	N/A	1, 17
THREADSTACK64	OFF,1M,1M,128M	N/A	N/A	N/A	30
TRACE	OFF,4K,DUMP, LE=0	OFF,4K,DUMP, LE=0	OFF,4K,DUMP, LE=0	OFF,4K,DUMP, LE=0	1
TRAP	ON,SPIE	ON,SPIE	ON,SPIE	ON,SPIE	1
UPSI	00000000	00000000	00000000	00000000	3
USRHDLR	NOUSRHDLR	User-defined	NOUSRHDLR	User-defined	1, 10, 28
VCTRSAVE	OFF	OFF	N/A	N/A	1
XPLINK	OFF	OFF	N/A	N/A	7, 12, 25, 26, 27, 32
XUFLOW	AUTO	AUTO	AUTO	AUTO	1

Table Notes:

1. This option is supported in all languages (C/C++, COBOL, Fortran, PL/I) and in environments where multiple (Multi) languages are used.
2. When running with IMS, this setting ensures that IMS transactions will be rolled back if errors occur in an application that is written in another Language Environment-enabled language; an abend causes IMS to rollback any database updates. When running a batch job, this setting ensures that a job step will abend if errors occur in an application that is written in another language.
3. This option is supported for COBOL only.
4. For PL/I, specify ALL31(OFF) for AMODE 24 programs. For COBOL, specify ALL31(OFF) if the applications contain one of the following:
 - A VS COBOL II NORES program (non-CICS program)
 - An OS/VS COBOL program (non-CICS program)
 - An AMODE 24 program

If you use ALL31(OFF), you must also specify STACK(,,BELOW,,,); AMODE 24 programs usually require stack storage below the 16M line.
5. If your installation uses Fortran in a multi-language environment, use the recommended setting for Fortran.
6. This option is supported for C only; it is not supported in C++.
7. You cannot set this option during Language Environment installation (CEEEOPT, CEEDOPT, or CEEROPT), in a CEEPRMxx parmlib member, or with a SETCEE command.
8. This option is supported for Fortran only.
9. This option can only be specified in CEEUOPT and CEEDOPT during Language Environment initialization.
10. There is no standard recommended value for this option; specify an appropriate value according to the needs of your installation.
11. Specify this option only when developing and debugging applications.
12. This option is supported for C/C++ only.
13. This option is supported for C/C++ and Enterprise PL/I only.

Run-time option summary

14. For tuning and performance information about the HEAPPOOLS run-time option, see *z/OS Language Environment Programming Guide*.
15. If your installation uses COBOL in a multi-language environment, use the recommended option setting for COBOL.
16. Specify any name for the message output file. For Fortran applications, specify MSGFILE(FT06F001) to produce the same ddname as in VS Fortran.
17. For single-tasking PL/I applications, use the recommended Language Environment default. However, for multitasking PL/I applications, the following setting is recommended: THREADSTACK(4K,4K,BELOW,KEEP,,).
18. This option is supported for PL/I for MVS only.
19. If the TEST run-time option is in effect when you specify a value on the PROFILE run-time option, Language Environment will ignore the PROFILE value.
20. For C/C++ applications running with ALL31(OFF) or OS PL/I applications that have not been relinked, you must specify STACK(,BELOW,,) to ensure that stack storage is addressable by the application.

21. For CICS:

UATRACE option will produce a Language Environment-formatted dump (CEEDUMP) which includes traceback information, and it will produce a CICS transaction dump. This recommendation applies to those customers that wish to maintain compatibility with the VS COBOL II default option of STAE in a CICS environment.

If a traceback CEEDUMP is not needed by the application environment (either because the COBOL II option of NOSTAE used to be implemented or if that dump is unused in any of the other member language application environments) use TERMTHDACT(MSG) to eliminate the performance overhead of writing formatted CEEDUMPs to the CESE CICS transient data queue.

For Non-CICS:

Specify UADUMP to obtain a system dump and a Language Environment-formatted dump which includes traceback information and a dump of control blocks and various levels of storage. This is only recommended if the TRACE dump is insufficient for debugging the application.

For more information, see the following books:

- *z/OS Language Environment Customization*
- *Enterprise COBOL for z/OS, V4R2, Compiler and Runtime Migration Guide, GC23-8527*
- *Enterprise COBOL for z/OS, V3R4, Compiler and Runtime Migration Guide, GC27-1409*

22. To get behavior that is similar to the VS COBOL II run-time option WSCLEAR, use STORAGE(00,NONE,NONE,0K) for non-CICS and CICS applications.

Recommendation: You should **not** use STORAGE(NONE,NONE,00,0K). Although it initializes variables for C and PL/I applications, serious performance degradation can occur. C and PL/I programs should be changed to initialize their own variables.

23. Values 512K, and 128K represent dsinit_size and dsincr_size, the amounts of storage that can be used for downward growing stack frames (plus stack header, approximately 20 bytes). The actual size of the storage getmained will be 4K larger to accommodate the guard page. The downward growing stack is

only initialized in an XPLINK supported environment and when an XPLINK application is active in the enclave, otherwise the `dsinit_size` and `dsincr_size` are ignored.

24. The behavior of the `dsa_alloc_value` sub-option of the `STORAGE` runtime option will be different for an XPLINK stack. The `dsa` will only be initialized for routines that perform an explicit check for stack overflow. For C/C++, the compiler option `XPLINK(NOGUARD)` can be used to force the compiler to generate prologs with explicit checks for stack overflow.
25. The `ALL31` runtime option will be forced to `ON` when the `XPLINK(ON)` run-time option is specified, or at least one XPLINK routine is present in the enclave. No message will be issued to indicate this action.
26. If the XPLINK run-time option is not specified and the initial program contains at least one XPLINK-compiled part, then the XPLINK run-time option will be forced to `ON`. No message will be issued to indicate this action.
27. When the `XPLINK(ON)` run-time option is specified or at least one XPLINK routine is present in the enclave, the `STACK` run-time option will forced to `STACK(,ANY,,)`. No message will be issued to indicate this action.
28. IBM supplies a sample user-written condition handler found in `SCEESAMP` called `CEEWUCHA`. Under CICS, this handler will give you similar abend codes that were around in certain pre-Language Environment environments. The `CEEWUCHA` load module needs to be build using `CEEWWCHA` provided in `SCEESAMP`. Please be aware that this handler has support for both COBOL and PL/I and is shipped with the PL/I specific behavior commented out. If you want this PL/I behavior, modify the source before using `CEEWWCHA`.
29. Acquiring a storage increment often involves a new storage obtain.
Recommendations: The increment size (4080 is recommended) should be 16 bytes less than the exact size of one or more pages to account for the 16-byte check zone that CICS applies to all storage obtain requests. This keeps Language Environment from obtaining an extra page of storage beyond the requested amount. This is important in CICS environments where storage below the line is especially constrained. The initial size in a CICS environment is part of a larger storage obtain that includes other storage required for Language Environment during initialization. Therefore, you can specify the initial size as exactly one or more pages, for example, 4K, 8K, and so forth, without concern for acquiring an extra page.
30. This option is supported for AMODE 64 only.
31. You should not use `STORAGE(,00)` in any performance-critical application.
32. You cannot specify this option with the `CEEBXITA` assembler user exit interface.

|
|

Run-time option summary

Chapter 5. Other HLL migration considerations

This topic includes migration concerns that are language-specific, such as: differences in how Language Environment and an HLL handle return codes, run-time messages, entry files, and user exits. For more information about these considerations, see the following informations:

- *z/OS XL C/C++ Compiler and Run-Time Migration Guide for the Application Programmer*
- *Enterprise COBOL for z/OS, V4R2, Compiler and Runtime Migration Guide, GC23-8527, or Enterprise COBOL for z/OS, V3R4, Compiler and Runtime Migration Guide, GC27-1409*
- *Enterprise PL/I for z/OS, V3R9, Migration Guide or PL/I for MVS & VM Compiler and Run-Time Migration Guide*
- *z/OS Language Environment Programming Guide*

C considerations

The following topics list some sample migration problems. For a complete list of migration considerations, see one of the C migration guides listed in the preceding topic.

Standard streams

Under z/OS Language Environment there is no longer an automatic association of ddnames SYSTERM, SYSERR, SYSPRINT with stderr. Command line redirection of the type 1>&2 is necessary in batch to cause stderr and stdout to share a device.

In C/370 Version 1 and Version 2, you could override the destination of error messages by redirecting stderr. Language Environment determines the destination of all messages from the new MSGFILE run-time option. For more information about the MSGFILE option, see *z/OS Language Environment Programming Guide*.

Passing command line parameters

In C/370 Version 1 or Version 2, if an error was detected with the parameters being passed to the main program, the program terminated with a return code of 8 and a message indicating the reason the program terminated. For example, if there was an error in the redirection parameters, the message would indicate that the program had terminated because of a redirection error. Under Language Environment, the same message is displayed, but the program also terminates with a 4093 abend, reason code 52 (X'34'). For more information about reason codes, see *z/OS Language Environment Debugging Guide*.

User exits

If CEEBXITA and IBMBXITA are present in a relinked C/370 Version 1 or Version 2 module, CEEBXITA will take precedence over IBMBXITA.

Time functions

If you are migrating from IBM C/370 (Version 1 or Version 2) or AD/Cycle C/370 (Version 1 Release 1 or Version 1 Release 2), you should be aware of the following change in time functions.

Other considerations

- The `ctime()`, `localtime()`, and `mktime()` functions will return Coordinated Universal Time (UTC) time unless customized locale information is available. When you customize the locale, time functions preserve the time and date and correctly adjust for daylight time on a given date. See *z/OS XL C/C++ Programming Guide* for more information about environment variables and customizing locale information.
- In POSIX and non-POSIX applications, you can use the `TZ` environment variable to supply the necessary time zone information for your location. Previously, for non-POSIX applications, you could supply customized locale information only by setting time zone and daylight information in the `LC_TOD` locale category.

Load modules that invoke a Debugging Tool

C/370 library application load modules that use `ctest()` to invoke the Debug Tool must be relinked to run with Language Environment. The old library object, `@@CTEST`, must be replaced, as described in *z/OS XL C/C++ Compiler and Run-Time Migration Guide for the Application Programmer* and *IBM C for VM/ESA Compiler and Run-Time Migration Guide*. After you replace the old objects, the new modules will run with Language Environment.

Prefix of `perror()` and `strerror()` messages in C

With Language Environment, all `perror()` and `strerror()` messages in C contain a prefix. With C/370 Version 1 and Version 2 there was no prefix on these messages. The prefix is `EDCxxxxa`, where `xxxx` is a number (always `5xxx`) and the `a` is I, W, or E. See *z/OS Language Environment Run-Time Messages* for a list of messages.

AMODE errors from ILCs

In ILC applications of C/370 Version 1 or Version 2 and VS COBOL II, if C/370 was running at AMODE 31 and COBOL was running at AMODE 24, an error was produced (2052) and the application failed. Under Language Environment, the call will fail but the message will be `EDC5052`, protection exception.

PL/I considerations

The following topics describe some of the items you should consider when migrating PL/I applications to Language Environment.

Dumps

The output produced by `PLIDUMP` is different when running under Language Environment. For detailed information, see *VisualAge PL/I for OS/390 Compiler and Run-Time Migration Guide*, *Enterprise PL/I for z/OS, V3R9, Migration Guide* or *PL/I for MVS & VM Compiler and Run-Time Migration Guide*.

Condition handling

In general, PL/I condition handling functions in the same way when running under Language Environment. However, the issuing of diagnostic messages may vary. For example, the diagnostic message for an `ERROR` condition is issued only if there is no `ERROR ON-unit` established, or if the `ERROR ON-unit` does not recover from the condition by using a `GOTO` out of block. However, for other PL/I conditions whose implicit action includes printing a message and raising the `ERROR` condition, the message is issued before control is given to an established `ERROR ON-unit`.

User exits

The OS PL/I Version 2 assembler user exits IBMBXITA and IBMFXITA are supported by PL/I for MVS & VM for compatibility. However, the Language Environment user exit CEEBINT should be used instead. Only CEEBINT is supported by VisualAge PL/I for OS/390.

Also, the OS PL/I Version 2 high-level language user exit IBMBINT is not recommended; it is supported only for compatibility. Use the Language Environment high-level language user exit, CEEBINT, instead. Only CEEBXITA is supported by VisualAge PL/I for OS/390. See *VisualAge PL/I for OS/390 Compiler and Run-Time Migration Guide, Enterprise PL/I for z/OS, V3R9, Migration Guide* or *PL/I for MVS & VM Compiler and Run-Time Migration Guide* for detailed information. See *z/OS Language Environment Programming Guide* for more information about the Language Environment user exits.

SYSPRINT

In PL/I, run-time messages are directed, by default, to the Language Environment MSGFILE rather than to SYSPRINT. Run-time user output is still directed to SYSPRINT. If you want run-time messages to go to SYSPRINT, specify the MSGFILE(SYSPRINT) run-time option. In this case, SYSPRINT can contain both user output and run-time output. For more information about the MSGFILE run-time option, see *z/OS Language Environment Programming Reference*.

If you specify a RECSIZE value that is not consistent with the LRECL of the data set or with the LRECL on the DD statement, the PL/I run-time library will diagnose this with an UNDEFINEDFILE condition with ONCODE=81. You must change the JCL to ensure that the values are the same or remove the LRECL value from the DD statement.

For DB2 UDB for z/OS Version 8 and DB2 Version 9.1 for z/OS customers, job steps that execute program DSNTEP2 or DSNTEP4 will experience user abend 4038. The user abend 4038 happens because UNDEFINEDFILE condition with ONCODE=81 error when the SYSPRINT DD specifies an LRECL that does not match the RECSIZE specified by DSNTEP2 and DSNTEP4 in the PAGEWIDTH constant. PAGEWIDTH is typically 133 but can be changed in the source code for DSNTEP2 and DSNTEP4. If you experience the abend and do not know the PAGEWIDTH setting, remove the LRECL from the SYSPRINT DD in job steps that execute DSNTEP2 or DSNTEP4.

Format and content of messages

The format and content of run-time messages is different for PL/I applications that run with Language Environment. Differences include the following items:

- The message number in the message prefix is now four digits instead of three digits.
- The message severity in the message prefix can now be C, E, I, S, or W.
- The message text of some mixed-case English and Japanese messages has been enhanced.

You must modify your applications if they analyze the run-time output. See *z/OS Language Environment Programming Reference* for more information about using and handling messages.

Other considerations

VisualAge PL/I for OS/390 object compatibility

Certain restrictions apply to load modules containing a mixture of VisualAge PL/I for OS/390 objects, and objects produced by earlier compilers (for example OS PL/I and PL/I for MVS & VM). For best results, do not mix compiler levels in a load module. See *VisualAge PL/I for OS/390 Compiler and Run-Time Migration Guide* or *Enterprise PL/I for z/OS, V3R9, Migration Guide* for more information.

General considerations

This topic describes other items you should consider when migrating a pre-Language Environment HLL application to an application that conforms to Language Environment.

Return and reason codes

Some return and reason codes will differ when running under Language Environment. JCL and EXECs that are affected by them must be changed accordingly. See *z/OS Language Environment Debugging Guide* information for details about return and reason codes.

Storage reports

The output of the run-time storage report is different when running with Language Environment. For information about the RPTSTG run-time option, see *z/OS Language Environment Programming Reference*. For an example of the storage report, see *z/OS Language Environment Debugging Guide*.

Stream I/O

If you choose the LINESIZE option, and you provide a record size value that is too small to hold the LINESIZE (taking into account the record format and appropriate control byte overhead), the UNDEFINEDFILE condition is raised.

This behavior is different from previous Language Environment releases. In previous releases, the following was true:

For DD SYSOUT= files except SYSPRINT, if you chose the LINESIZE option, and you provided a record size value that is too small to hold the LINESIZE (taking into account the record format and appropriate control byte overhead), the LINESIZE is used to determine a new record size that matched the given LINESIZE. For DD DSN= files, the UNDEFINEDFILE condition is raised.

Appendix A. Language Environment-enabled vendor tools and application packages

Language Environment for z/OS is IBM's common run-time environment for enterprise applications written in COBOL, C/C++, PL/I, and FORTRAN. Language Environment provides interlanguage communication for modules written in different languages as well as a consistent run-time environment for essential services, such as initialization, termination, message handling, National Language, and storage management. In addition, Language Environment provides common exception-handling services resulting in improved reliability and better failure diagnosis.

Customers with IBM compilers and tools also have third party vendor tools and application packages installed. IBM recognizes the following in upgrading the languages:

- **C/C++** — Many IBM products (for example BookManager, TCP/IP, and others) and third party vendor tools and application packages are built using C.
- **COBOL** — Some of the third party vendor tools and application packages do not run with Language Environment. Customers will upgrade their COBOL when their existing tools and application packages run in the new Language Environment.
- **FORTTRAN** — Fortran is now available in Language Environment, which allows Interlanguage Communication (ILC) calls into Fortran modules from C, COBOL, and PL/I.
- **PL/I** — Many IBM products (for example NetView) and third party vendor tools and application packages are built using PL/I.

This appendix includes information about other companies' products. Such information was obtained from the respective manufacturers of such products or their published announcements. The user should validate any information depicted here by contacting the appropriate manufacturer for the most current information on the product(s) in their particular situation.

IBM is not responsible for other companies' products, and IBM cannot confirm any claims regarding other companies' products. IBM IS PROVIDING THE INFORMATION IN THIS APPENDIX ON AN "AS IS" BASIS, AND EXPRESSLY DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE USER OF THIS INFORMATION AGREES THAT IBM WILL HAVE NO LIABILITY FOR ANY DAMAGES WHATSOEVER OR FOR ANY OTHER CONSEQUENCES RESULTING FROM THE USE OF THIS INFORMATION.

Below is the legend for the Enabled column in the tables contained in this appendix.

Entry	Meaning
Yes	The product works with Language Environment. Note: Check comments for release level or needed service.
No	The product requires a run-time library, but does not work with Language Environment.

Enabled vendor tools

Entry	Meaning
N/A	The product does not use a run-time library for the languages supported by Language Environment.
?	The product requires a run-time library, but it is unknown if it will work with Language Environment.

IBM Corporation

NAME:	IBM Corp.
ADDRESS:	Old Orchard Rd. Armonk, NY 10504
PHONE:	(800) IBM-4-YOU
DIRECT SALES:	(800) 426-2968 (IBM Direct) or Local IBM Branch Office
TECH SUPPORT:	(800) 237-5511
WEB SITE:	http://www.ibm.com

z/OS

For individual elements or features of z/OS that require Language Environment, please refer to *z/OS Program Directory*.

Products

Product	Enabled	Comments
ACF Network Control Program (ACF/NCP)	N/A	Runs in a communications controller, not on the host
ACF/VTAM for MVS	Yes	VTAM V4R3 is Language Environment-enabled for the following functions: <ul style="list-style-type: none"> • Network Management Agent
ACF/VTAM for VM	No	No plans for support
AD/Cycle C/370 compiler Version 1.2	Yes	
ADSTAR Distributed Storage Manager (ADSM) (MVS/ESA)	Yes	
AFP ToolBox for MVS (5655-A25)	Yes	Requires Language Environment
AIX Distributed Computing Environment/ESA (DCE/ESA) (AIX/ESA)	Yes	Enabled since V1R1
ANo/MVS (5756-265)	No	Replaced by 5695-178
ANo/MVS (5695-178)	Yes	
ANYNET (MVS/ESA)	Yes	Feature of VTAM V4R3
Automated Operations Control/MVS (AOC/MVS)	No	No plans for support; replaced by System Automation for MVS

Enabled vendor tools

Product	Enabled	Comments
Application System (AS) (MVS/ESA, VM)	Yes	AS IC/E is Language Environment-enabled for V3 with APAR PN68743 that contains 4 PTF's: IC/E (MVS) V3.1 UN74167, IC/E (VM) V3.1 UN74168, IC/E (MVS) V3.2 UN74169 and IC/E (VM) V3.2 UN74170. AS IC/E is Language Environment-enabled for V4 with APAR PN68833 that contains 2 PTF's: IC/E (MVS) V4.1 UN74171 and IC/E (VM) V4.1 UN74172.
Application Support Facility (ASF) for MVS (MVS/ESA)	Yes	ASF V3R1 is Language Environment-enabled; IMS support requires PN74705
Basic Telecommunication Access Method (BTAM) (5665-279)	N/A	Does not require a run-time library
BookManager/MVS (MVS/ESA)	Yes	BookManager/MVS 1.3 is Language Environment-enabled
BookManager/VM	Yes	BookManager/VM 1.3 is Language Environment-enabled with APAR GC05334
Bulk Data Transfer (BDT) (5696-PKK)	N/A	Does not require a run-time library
CACHE RMF Reporter (DQD-5798)	?	This PO is written in PL/I. The function provided by this PO is now integrated with the RMF postprocessor reports. It is no longer being developed or supported and has not been tested with Language Environment.
C/C++ for MVS/ESA V3R2	Yes	
OS/390 C/C++	Yes	
CICS/MTCS	Yes	No known Language Environment dependencies
CICS/MVS 3270 Format Utility	No	Discontinued service 12/31/96
CICS/VSAM Recovery	Yes	Enabled since V2R2
CLIO/S	Yes	
COBOL CICS Conversion AID (CCCA)	Yes	Enabled since R2 for MVS
COBOL Structuring Facility	Yes	Enabled since V3R1
Cross System Product (CSP) (5688-218, 5688-206)	Yes	CSP V4R1 will work with Language Environment. Be sure CSP APARS PN64541, PN60042 and Language Environment APAR PN60776 are on your system. CSP V3R3 and earlier releases do not require a run-time library.
Customer Information Control System/ESA (CICS/ESA) (MVS/ESA)	Yes	Enabled since V3R3
Data Interchange	N/A	Does not require a run-time library
DB2 (5665-DB2)	N/A	Does not require a run-time library
Data Base Edit Facility (DBEDIT) (MVS/ESA)	Yes	PN60210 contains Language Environment enablement instructions

Enabled vendor tools

Product	Enabled	Comments
Data Facility Sort (DFSORT) (MVS/ESA)	Yes	Enabled since R12
Device Support Facility (DSF) (5655-257)	N/A	Does not require a run-time library
DFSMSdftp	Yes	Only if you plan on using CDRA in DFSMS 1.3 and upward
DFSMSdss	N/A	Does not require a run-time library
DFSMSshsm	N/A	Does not require a run-time library
DFSMSrmm	N/A	Does not require a run-time library
DI/MVS	Yes	
DISOSS (5665-290)	N/A	Does not require a run-time library
DISOSS Library Services Extended (DLS-E) (5787-ECH)	Yes	APAR HC06749 for DLS-E required to run with Language Environment
DITTO (5798-ARD)	N/A	Does not require a run-time library
Document Composition Facility (DCF/MVS)	Yes	DCF/MVS is Language Environment-enabled with STACK option for ODF support. The remainder of DCF has no run-time dependency.
Document Composition Facility (DCF/VM)	Yes	DCF/VM is Language Environment-enabled with APAR PN61308 for ODF support. The remainder of DCF has no run-time dependency.
DisplayWrite/370 (DW/370)	N/A	Does not require a run-time library
DPAM	No	No plans for support
DROP/R Capture MVS	Yes	
Emulator Program (EP)	N/A	Runs in a communications controller, not on a host
Environment Error Recording Program (5658-260)	N/A	Does not require a run-time library
ESCON Manager (ESCM) (5688-008)	No	Replaced by System Automation for MVS
Graph Data Display Manager (GDDM) (5665-356)	N/A	Does not require a run-time library
GDDM IMD (5665-356)	N/A	Does not require a run-time library
GDDM Program Graphic Feature (GDDM-PGF)	N/A	Does not require a run-time library
Hardware Configuration Definition (HCD)	Yes	
Host Communication Facility (HCF) (5668-985)	N/A	Does not require a run-time library
ICF Catalog Recovery (5798-DXQ)	N/A	Does not require a run-time library
IMS Application Development Facility (IMSADF)	Yes	IMSADF V2R2 is Language Environment-enabled with APAR PN84976
IBM Print Services Facility (PSF/MVS) (MVS/ESA)	Yes	Enabled since V2

Enabled vendor tools

Product	Enabled	Comments
Image Object Distribution Manager (IODM)	No	Plans being developed to support Language Environment
Image/Plus Folder Application Facility (IPFAF)	No	Plans being developed
IMS/ESA	Yes	
IMS System Utilities	Yes	
InfoMan		Only 2 parts of InfoMan require Language Environment, the Graphics Module and the NetView Bridge Adapter. The Graphics Module V5R1 and above work with Language Environment. The NetView Bridge Adapter requires NetView and does not work with Language Environment.
Inforem III	Yes	
Information Management System/ESA (IMS/ESA) Database Manager and IMS/ESA Transaction Manager	Yes	Enabled since V1R3
Interactive System Product Facility (ISPF) (5655-042)	N/A	Does not require a run-time library
Item Access Facility MVS/ESA (IAFC) (MVS/ESA)	No	Migration guide available; send a request to Language Environment Feedback via the Web
Job Entry Subsystem (JES) (5695-047)	N/A	Does not require a run-time library
Jes328X Printing Subsystem	N/A	Does not require a run-time library
KnowledgeTool (MVS/ESA)	No	Product has no plans of relinking with Language Environment. Therefore it is not Language Environment-enabled.
MQSeries (MVS/ESA)	Yes	
NetView (MVS/ESA)	Yes	NetView V3R2 or TME10 NetView
NetView/GMFHS (MVS/ESA)	Yes	
NetView/RODM (MVS/ESA)	Yes	
NetView Access (5665-365)	N/A	Does not require a run-time library
NetView Distribution Manager (NDM)	N/A	Does not require a run-time library
NetView File Transfer Program (NetView FTP)	N/A	Does not require a run-time library
NetView Performance Manager (NPM) (5655-043)	N/A	Does not require a run-time library
NPSI (5688-035)	N/A	Runs on a communications controller, not on a host
NTUNEMON (NCP Monitor Tool)	N/A	Does not require a run-time library
NTUNENCP (NCP Tuning Tool)	N/A	Does not require a run-time library
OfficeVision/MVS (MVS/ESA)	Yes	Enabled since V1R3
OfficeVision/VM	Yes	

Enabled vendor tools

Product	Enabled	Comments
z/OS UNIX System Services	Yes	
Overlay Generation Language/370 (OGL) (5688-191)	N/A	Does not require a run-time library
Page Printing Formatting Aid/370 (PPFA/370) (5688-190)	N/A	Does not require a run-time library
PC/TSO File Transfer Product (PC/TSO FTP)	N/A	Does not require a run-time library
Print Facility (VMPRF)	Yes	VMPRF is Language Environment-enabled with APAR VM59419
PagePrinterMigrationProgram (PPMP) (MVS/ESA) (5695-040)	Yes	Need to apply PTF UW43230
Resource Measurement Facility (RMF) (MVS/ESA)	N/A	Does not require a run-time library
ScreenView (5695-047)	N/A	Does not require a run-time library. This product is out of service for VM, VSE and MVS.
SearchManager/370 for MVS (5695-070)	Yes	Enabled since R3. R3 requires APARs PN73137 and PN76260.
SGML Translator (5684-025)	No	SGML Translator is not planning to support Language Environment
System Automation for MVS	No	No plans to support Language Environment
z/OS Transmission Control Protocol/Internet Protocol (TCP/IP)	Yes	Enabled since V3R1
Transmission Control Protocol/Internet Protocol (TCP/IP) for VM	No	
TSCF (MVS/ESA)	No	Replaced by System Automation for MVS
VisualAge Generator (MVS/ESA)	Yes	Formerly known as VisualGen
VisualInfo (MVS/ESA)	Yes	VisualInfo V2 works with Language Environment R5 and APAR PN81700

Action Software International

NAME: Action Software International (a division of Mazda Computer Corporation)

ADDRESS: 20 Valleywood Drive, Suite 107 Markham, ON L3R 6G1 Canada

PHONE: (905) 470-7113

FAX: (905) 470-6507

TECH SUPPORT: (905) 470-7113 (E-mail: change@actionsoftware.com)

Product	Enabled	Comments
Change Action	N/A	No known Language Environment dependencies

ADPAC Corp.

NAME: ADPAC Corp.
ADDRESS: 425 Market St., Suite 400 San, Francisco, CA 94105
PHONE: (415) 777-5400
FAX: (415) 284-1126
WEB SITE: <http://www.adpac.com>

Product	Enabled	Comments
Programming Maintenance/Standard Solution (PM/SS) (MVS/ESA)	Yes	
System Vision Impact Analysis	Yes	
System Vision JCL VIEW	Yes	
System Vision Program Inventory	Yes	
System Vision Upgrade Unit	Yes	

Advantis

NAME: Advantis
ADDRESS: 3405 West Dr. Martin Luther King Jr. Blvd., P.O. Box 30021, Tampa, FL 33630
PHONE: (800) 727-2222
WEB SITE: <http://www.advantis.com>

Product	Enabled	Comments
Expedite Base MVS	N/A	Does not require a run-time library
Expedite CICS for MVS	Yes	

Advisor Technology Services

NAME: Advisor Technology Services (Formerly Broadway and Seymour, Inc.) (Formerly Trust Systems, Inc.)
ADDRESS: 128 South Tryon St., Charlotte, NC 28202
PHONE: (800) 836-6575
TECH SUPPORT: (800) 743-2505
WEB SITE: None. In process of developing one (2/6/97 status).

Product	Enabled	Comments
AMtrust (MVS/ESA)	Yes	

Alltel Corp.

NAME: Alltel Corp.
ADDRESS: One Allied Drive, Little Rock, AR 72202
PHONE: (501) 661-8000
FAX: (501) 661-8487
WEB SITE: <http://www.alltel.com>

Product	Enabled	Comments
Systematics Financial & Health Care Packages	No	Have worked with customers on work around
TDS Healthcare Packages (Eclipsis Corp.)	?	Language Environment status not known

American Software, Inc.

NAME: American Software, Inc.
ADDRESS: 470 E. Paces Ferry Rd., Atlanta, GA 30305
PHONE: (404) 261-4381
FAX: (404) 264-5394
WEB SITE: <http://www.amsoftware.com>

Product	Enabled	Comments
AMSOFT (MVS/ESA)	Yes	
Distribution Requirements Planning (MVS/ESA)	Yes	
MRP-8 Manufacturing Resource Planning (MVS/ESA)	Yes	

ANSYS, Inc.

NAME: ANSYS, Inc.
ADDRESS: 275 Technology Drive, Canonsburg, PA 15317
PHONE: (412) 746-3304
FAX: (412) 514-9494
WEB SITE: <http://www.ansys.com>

Product	Enabled	Comments
ANSYS	N/A	Language Environment not required, ships FORTRAN runtime

Applications Software, Inc.

NAME: Applications Software, Inc.

ADDRESS: 5455 Garden Grove Blvd., Suite 500, Westminister, CA 92683
PHONE: (714) 891-2616
FAX: (714) 895-5690
TECH SUPPORT: (860) 675-8158
WEB SITE: None

Product	Enabled	Comments
ASI-ST (MVS/ESA)	N/A	Written totally in assembler; does not require a run-time library

Candle

NAME: **Candle**
ADDRESS: 2425 Olympic Blvd., Santa Monica, CA 90404
PHONE: (800) 843-3970 or (310) 829-5800
FAX: (310) 582-4287
TECH SUPPORT: (800) 328-1811
WEB SITE: <http://www.candle.com>

Product	Enabled	Comments
CL/GATEWAY	Yes	No Language Environment dependencies; no known problems
CL/SUPERSESSION	Yes	No Language Environment dependencies; no known problems
Omegamon for CICS/v300 (MVS/ESA)	Yes	Language Environment-enabled for compatibility
Omegamon II/v300 (MVS/ESA)	Yes	

Chicago-Soft, Ltd.

NAME: **Chicago-Soft, Ltd.**
ADDRESS: Maple St., Hanover, NH 03755
PHONE: (603) 643-4002
 Direct Sales: (603) 643-4002
FAX: (773) 282-9036
TECH SUPPORT: (773) 282-4777
WEB SITE: <http://www.chicago-soft.com>

Product	Enabled	Comments
MVS/QuickRef	N/A	Does not require a run-time library

CHI/COR Information Management, Inc

NAME: CHI/COR Information Management, Inc
ADDRESS: 300 South Wacker Drive, Chicago, IL 60606
PHONE: (312) 322-0150
WEB SITE: <http://www.chicor.com>

Product	Enabled	Comments
Deduction Management System (MVS/ESA)	N/A	Written in RPG; doesn't use Language Environment

CINCOM Systems, Inc

NAME: CINCOM Systems, Inc.
ADDRESS: 2300 Montana Avenue, Cincinnati, OH 45211-3899
PHONE: (513) 612-2300
FAX: (513) 481-8332
WEB SITE: <http://www.cincom.com>

Product	Enabled	Comments
MAN Series M/TEXT (MVS/ESA)	N/A	Does not require a run-time library
MANTIS (MVS/ESA)	No	Language Environment enablement under discussion (status as of 1/27/97)

Computer Associates International, Inc.

NAME: Computer Associates International, Inc.
ADDRESS: One Computer Associates Plaza, Islandia, NY 11788-7000
PHONE: (800) CALL-CAI or (516) 342-5224
FAX: (516) 342-5734
WEB SITE: <http://www.cai.com>

Product	Enabled	Comments
CA-APCDDS	N/A	No Language Environment dependencies; no known problems
CA-APC/DOC	N/A	No Language Environment dependencies; no known problems
CA-DADS/PLUS	N/A	No Language Environment dependencies; no known problems
CA-Datacom/CICS Services	Yes	Works in Language Environment environment; no known problems
CA-Datacom/Extended SQL Option	Yes	Works in Language Environment environment; no known problems

Enabled vendor tools

Product	Enabled	Comments
CA-Datacom/DB	Yes	Works in Language Environment environment; no Language Environment dependencies
CA-Datacom/DB Datadictionary	Yes	Works in Language Environment environment; no known problems
CA-Datacom/DLI Transparency	Yes	Works in Language Environment environment; no known problems
CA-Datacom/IMS/DC Services	N/A	Does not require a run-time library
CA-Datacom/Total Transparency	Yes	Works in Language Environment environment; no known problems
CA-Datacom/VSAM Transparency	N/A	Does not require a run-time library
CA-Data Query	Yes	Works in Language Environment environment; no known problems
CA-DISPATCH	N/A	No Language Environment dependencies; no known problems
CA-DOCVIEW	N/A	No Language Environment dependencies; no known problems
CA-EASYTREVE	Y	EasyTreve 6.0 works with Language Environment compatibility mode
CA-EXAMINE	N/A	No Language Environment dependencies; no known problems
CA-EZT+	Yes	Language Environment dependencies occur when subroutines or exits are used which are written in a language using Language Environment as their run-time environment. This situation may be triggered by using CALL-statements or by using file I/O exits from within an EZT+ program. To bypass, 1) call IGZERRE before invoking your subprogram or exit, or 2) use the RTEREUS run-time option.
CA-EZT/DB2	N/A	No Language Environment dependencies; no known problems
CA-EZT/IMS	N/A	No Language Environment dependencies; no known problems
CA-EZTEST/CICS/3.4 (MVS/ESA)	Yes	
CA-FILESAVE/RCS	N/A	No Language Environment dependencies; no known problems
CA-IDMS (MVS/ESA)	Yes	Release 12.0 is Language Environment-enabled
CA-INSIGHT/DB2	N/A	No Language Environment dependencies; no known problems
CA-InterTest 5.3 (MVS/ESA)	Yes	Language Environment-enabled for LE/370 V1 R1 and above
CA-JCL/CHECK	N/A	No Language Environment dependencies; no known problems
CA-LIBRARIAN (MVS/ESA)	Yes	

Enabled vendor tools

Product	Enabled	Comments
CA-LSERV	N/A	No Language Environment dependencies; no known problems
CA-Masterpiece (MVS/ESA)	Yes	
CA-Netman (MVS/ESA)	Yes	LE/370 1.2 enabled with CA APAR A94256AK0. LE/370 1.3 enabled with fixes T5VR195 and T5VR196 from CA.
CA-OPERA	N/A	No Language Environment dependencies; no known problems
CA-OPTIMIZER (MVS/ESA)	Yes	OS/VS COBOL programs compiled with CA OPTIMIZER using DETECT or ANALYZE optimizer options and run under Language Environment will receive an abend 0C4 in CA OPTIMIZER module CPXEM. Contact CA customer support for CA fix T5U2468. This fix is for CA-Optimizer 6.0 only. Per CA, user cannot compile with DETECT or ANALYZE options and run under Language Environment.
CA-PANVALET (MVS/ESA)	Yes	
CA-PMO	Yes	There is a performance problem — fix available from CA.
CA-ROSCOE (MVS/ESA)	Yes	
CA-SYMDUMP	Yes	CA-SYMDUMP 5.3 works with Language Environment
CA-TELON (MVS/ESA)	Yes	Will work with Language Environment if CA-TELON is at GEN9706 or later (Problem with PL/I - fix available from CA)
CA-TLMS	N/A	No Language Environment dependencies; no known problems
CA-VERIFY	N/A	No Language Environment dependencies; no known problems
CA-1	N/A	No Language Environment dependencies; no known problems
CA-7	N/A	No Language Environment dependencies; no known problems
CA-11	N/A	No Language Environment dependencies; no known problems
CA-90	Yes	
Endevor/Cross System Product (Endevor/CSP) (MVS/ESA)	Yes	
Endevor/DB (MVS/ESA)	Yes	
Endevor/DB2 (MVS/ESA)	Yes	
Endevor/MVS (MVS/ESA)	Yes	
Endevor Parallel Development Manager (MVS/ESA)	Yes	
RAMIS (MVS/ESA)	Yes	

Computer Corporation of America

NAME: Computer Corporation of America
ADDRESS: 500 Old Connecticut Path, Framingham, MA 01701
PHONE: (508) 270-6666
FAX: (508) 270-6688
TECH SUPPORT: (800) 755-4222
WEB SITE: <http://www.cca-int.com>

Product	Enabled	Comments
Model 204	Yes	3.2.0 is Language Environment-enabled

Compuware Corp.

NAME: Compuware Corp.
ADDRESS: One Campus Martius, Detroit, MI 48226
PHONE: (800) 521-9353 or (313) 227-7300
TECH SUPPORT: (800) 538-7822
WEB SITE: <http://www.compuware.com>

Product	Enabled	Comments
Abend-AID	Yes	For all products listed, consult web site for further information
Abend-AID for CICS	Yes	
Abend-AID for WebSphere MQ	Yes	.
File-AID/MVS (MVS/ESA)	Yes	
QAHiperstation	Yes	
QA Center WebSphere MQ	Yes	
QA Center Enterprise Servers	Yes	
STROBE	Yes	
Xpediter/CICS	Yes	
Xpediter/Code Coverage	Yes	
Xpediter/IMS	Yes	
Xpediter/TSO	Yes	
Xpediter/XChange	Yes	

Comshare, Inc.

NAME: Comshare, Inc.
ADDRESS: P. O. Box 1588, 555 Briarwood Circle, Ann Arbor, MI 48108
PHONE: (800) 922-7979 or (313) 994-4800
FAX: (313) 769-6943

Enabled vendor tools

TECH SUPPORT: (313) 994-5212
WEB SITE: <http://www.comshare.com>

Product	Enabled	Comments
Interactive Financial Planning System/Plus (IFPS/Plus) (MVS/ESA)	Yes	IFPS/Plus 5.01 is Language Environment-enabled

Data Kinetics, Ltd.

NAME: Data Kinetics, Ltd.
ADDRESS: 2460 Lancaster Road, Ottawa, Ontario Canada K1B 4S5
PHONE: (800) 267-0730 or (613) 523-5500
FAX: (613) 523-5533
TECH SUPPORT: (613) 523-5588
WEB SITE: <http://www.dkl.com>

Product	Enabled	Comments
tableBASE (MVS/ESA)	Yes	Language Environment-enabled

Deluxe Corp.

NAME: Deluxe Corp.
ADDRESS: 1050 County Road F West, St. Paul, MN 55126-2910
PHONE: (800) 328-9500
TECH SUPPORT: (800) 328-8434
WEB SITE: <http://www.deluxe.com>

Product	Enabled	Comments
Oneware	Yes	

Diversified Software Systems, Inc.

NAME: Diversified Software Systems, Inc.
ADDRESS: 18635 Sutter Blvd, Morgan Hill, CA 95037, USA
PHONE: (408) 778-9914
FAX: (408) 776-0382
TECH SUPPORT: (800) 273-3774 (719-265-6300) or www.diversifiedsoftware.com/contact/support.html
WEB SITE: <http://www.diversifiedsoftware.com>

Product	Enabled	Comments
PRO/JCL®	Yes	

Product	Enabled	Comments
INFO/X [®] Enterprise	Yes	
JOB/SCAN [™]	Yes	
DOCU/TEXT [®]	Yes	

Document Sciences Corporation

NAME: Document Sciences Corporation
ADDRESS: 6339 Paseo Del Lago, Carlsbad, CA 92009
PHONE: (760) 602-1400
FAX: (760) 602-1450
TECH SUPPORT: (760) 602-1500
WEB SITE: <http://www.docscience.com>

Product	Enabled	Comments
Compuset	Yes	
DLS	Yes	

Early, Cloud Solution Unit of IBM

NAME: Early, Cloud Solution Unit of IBM (Formerly Early, Cloud and Company)
ADDRESS: Aquidneck Industrial Park, Newport, RI 02840
PHONE: (800) 829-2050 or (401) 849-0500
WEB SITE: <http://www.earlycloud.com>

Product	Enabled	Comments
CallFlow	Yes	
Message Driven processor (MDp)	Yes	

Edge Information Group, Inc.

NAME: Edge Information Group, Inc.
ADDRESS: 1479 Business Center Drive, Suite 115, Mt. Prospect, IL 60056
PHONE: (847)297-2020
FAX: (847)297-2027
TECH SUPPORT: (513) 948-8906 or support@edge-information.com
WEB SITE: <http://www.edge-information.com>

Enabled vendor tools

Product	Enabled	Comments
Edge Portfolio Analyzer	N/A	The Edge Portfolio Analyzer is a tool to assist in migrating applications to Language Environment or to upgrade to new releases of z/OS or new releases of compilers. All releases of Language Environment and z/OS are supported, plus all COBOL, PL/I, C/C++ and FORTRAN compilers that generate code for all releases of z/OS.

EWO Software, Inc.

NAME: EWO Software, Inc.
ADDRESS: 358 Walter Avenue, Newbury Park, CA 91320
PHONE: (805) 498-8782
WEB SITE: <http://www.ewosoft.com>

Product	Enabled	Comments
Prescient Downloader	Yes	
Prescient Replicator	Yes	
Prescient Documentor	Yes	
Prescient Loadsycn	Yes	

Geac Host Technologies

NAME: Geac Host Technologies (Formerly Dun & Bradstreet Software)
ADDRESS: 66 Perimeter Center E., Atlanta, GA 30346
PHONE: (404) 239-2000 or (404) 239-INFO
TECH SUPPORT: (800) 808-3327 for E Series or (800) 808-1327 for M Series
WEB SITE: <http://www.geac.com>

Product	Enabled	Comments
Expert Series Applications (E Series)	Yes	
Millennium Series Applications (M Series)	Yes	

HBO & Co.

NAME: HBO & Co.
ADDRESS: 301 Perimeter Center N., Atlanta, GA 30346
PHONE: (770) 393-6000
TECH SUPPORT: (800) 962-HBOC
WEB SITE: <http://www.hboc.com>

Product	Enabled	Comments
Health Quest 2000 (MVS/ESA)	Yes	
Plus 2000 (MVS/ESA)	Yes	

Hogan Systems, Inc.

NAME: Hogan Systems, Inc.
ADDRESS: 5525 LBJ Freeway, Dallas, TX 75240
PHONE: (972) 386-0020
FAX: (972) 386-0315

Product	Enabled	Comments
Consumer and Merchant Servicing (MVS/ESA)	Yes	

HNC Software

NAME: HNC Software
ADDRESS: 5930 Cornerstone Court, West San Diego, CA 92121
PHONE: (619) 546-8877
WEB SITE: <http://www.hnc.com>

Product	Enabled	Comments
Falcon	Yes	Falcon has 2 load libraries, one for on-line and one for batch. Both work with Language Environment 1.5. Batch requires Language Environment maintenance level 9609.
Profitmax	?	Status unknown. None of their customers have run it with Language Environment.

Infodata Systems, Inc.

NAME: Infodata Systems, Inc.
ADDRESS: 12150 Monument Dr., Fairfax, VA 22033
PHONE: (703) 934-5205
FAX: (703) 934-7154
TECH SUPPORT: (703) 934-8149
WEB SITE: <http://www.infodata.com>

Product	Enabled	Comments
Inquire/Text (MVS/ESA)	Yes	Working on a fix as of 1/22/97
Shelf Space (MVS/ESA)	Yes	
Webb Inquire (MVS/ESA)	Yes	

Information Builders, Inc.

NAME: Information Builders, Inc.
ADDRESS: 1250 Broadway, New York, NY 10001
PHONE: (800) 969-INFO
FAX: (212) 967-6406
TECH SUPPORT: (800) 736-6130
WEB SITE: <http://www.informationbuilders.com>

Product	Enabled	Comments
Focus MVS	Yes	Minimum level 7.01. Recommended level 7.05.
Focus VM	Yes	Minimum level 7.01. Recommended level 7.05.

Information Retrieval Companies, Inc. (IRC Inc.)

NAME: Information Retrieval Companies, Inc.
ADDRESS: 3500A Regency Parkway. Cary, NC 27511
PHONE: (800) IRC-7768
FAX: (919) 460-7438
TECH SUPPORT: (919) 460-7446 x-135
WEB SITE: <http://www.ircsoft.com>

Product	Enabled	Comments
Automated Systems Information Management (MVS/ESA)	Yes	

Information Systems Of America, Inc.

NAME: Information Systems Of America, Inc. (Subsidiary of SunGard Insurance Systems, Inc.)
ADDRESS: 500 Northridge Rd., Atlanta, GA 30350
PHONE: (800) 659-4472 or (770) 587-6800
FAX: (770) 587-6808
WEB SITE: <http://www.sungard.com>

Product	Enabled	Comments
PRISM Investment Management & Accounting (MVS/ESA)	Yes	

Integral, Inc.

NAME: Integral, Inc.
ADDRESS: 2185 N. California Blvd., Walnut Creek, CA 94546
PHONE: (510) 939-3900
FAX: (510) 946-4891
WEB SITE: <http://www.integralsys.com>

Product	Enabled	Comments
Integral Human Resource System (MVS/ESA)	Yes	

Intersolv

NAME: Intersolv
ADDRESS: 9420 Key West Ave., Rockville, MD 20850
PHONE: (800) 582-1600
WEB SITE: <http://www.intersolv.com>

Product	Enabled	Comments
APS (MVS/ESA)	Yes	As of Version 4.0

ISOGON, Inc.

NAME: ISOGON, Inc.
ADDRESS: 330 Seventh Ave., New York, NY 10001
PHONE: (212) 376-3200
FAX: (212) 376-3280
TECH SUPPORT: (212) 376-3260
WEB SITE: <http://www.isogon.com>

Product	Enabled	Comments
Spiffy	N/A	No known Language Environment dependencies
Soft Audit/One	Yes	
Soft Audit/2000	Yes	
TICTOC	Yes	
License Power	Yes	

Lotus Development Corporation (An IBM Company)

NAME: Lotus Development Corporation
ADDRESS: 55 Cambridge Parkway, Cambridge, MA 02142
PHONE: (617) 577-8500

Enabled vendor tools

TECH SUPPORT: (610) 640-0700
WEB SITE: <http://www.lotus.com>

Product	Enabled	Comments
Softswitch Central (MVS/VM)	Yes	Enabled for VM 4.4.3 and above, and MVS 4.4.P2A and above

Macro 4 Inc.

NAME: **Macro 4 Inc.**
ADDRESS: 35 Waterview Boulevard, P.O. Box 292, Parsippany, NJ 07054-0292
PHONE: (973) 402-8000
FAX: (973) 402-7280
TECH SUPPORT: (973) 402-7360
WEB SITE: <http://www.macro4.com/dumpmaster>

Product	Enabled	Comments
Dumpmaster	Yes	Version Required 4.5.

MARBLE Computer, Inc.

NAME: **MARBLE Computer, Inc.**
ADDRESS: 160-4 Dover Road, Chichester, NH 03234
PHONE: (603) 798-4100
FAX: (603) 798-5100

Product	Enabled	Comments
Data Correlation and Documentation System (MVS/ESA)	Yes	

Merrill Consultants

NAME: **Merrill Consultants**
ADDRESS: 10717 Cromwell Drive, Dallas, TX 75229
PHONE: (214) 351-1966
FAX: (214) 350-3694
WEB SITE: <http://www.mxg.com>

Product	Enabled	Comments
MXG	N/A	No known Language Environment dependencies

Micro Focus, Inc.

NAME: Micro Focus, Inc.
ADDRESS: 2465 E. Bayshore Road, Suite 400, Palo Alto, CA 94303
PHONE: (800) 468-9080 or (415) 856-4161
FAX: (415) 856-6134
TECH SUPPORT: (415) 496-7230 or (610) 992-3550
WEB SITE: <http://www.microfocus.com>

Product	Enabled	Comments
Micro Focus COBOL Workbench	Yes	MF COBOL emulates COBOL/370 and support exists for source statements that utilize Language Environment services thru calls, but no Language Environment routines are provided.

Mobius Management Systems, Inc.

NAME: Mobius Management Systems, Inc.
ADDRESS: One Ramada Plaza, New Rochelle, NY 10801
PHONE: (914) 637-7200
WEB SITE: <http://www.mobius-inc.com>

Product	Enabled	Comments
INFOPAC-RDS	Yes	

National Technology Transfer Center

NAME: National Technology Transfer Center (Subsidiary of NASA Technology Transfer Div.)
ADDRESS: 316 Washington Ave., Wheeling, WV 26003
PHONE: (304) 243-2150
FAX: (304) 243-2539
WEB SITE: <http://www.nttc.edu/software>

Product	Enabled	Comments
NASTRAN (MVS/ESA)	No	No current plans for Language Environment support. Written in Fortran.

Panarama Software

NAME: Panarama Software
ADDRESS: 5550 Topanga Canyon Blvd. Third Floor, Woodland Hills, CA 91367
PHONE: (800) 829-7798 or (818) 710-7300

Enabled vendor tools

FAX: (818) 883-2338
WEB SITE: <http://www.pansoft.com>

Product	Enabled	Comments
Sunrise	N/A	Language Environment not required; ships SAS runtime.

Pegasystems, Inc.

NAME: Pegasystems, Inc.
ADDRESS: 101 Main Street, Cambridge, MA 02142
PHONE: (617) 374-9600
FAX: (617) 374-9620
WEB SITE: <http://www.pegasystems.com>

Product	Enabled	Comments
Pegasystems Banking Applications (MVS/ESA)	Yes	

Peregrine Systems, Inc.

NAME: Peregrine Systems, Inc.
ADDRESS: 12670 High Bluff Drive, San Diego, CA 92130
PHONE: (800) 638-5231 or (619) 481-5000
FAX: (619) 481-1751
WEB SITE: <http://www.peregrine.com>

Product	Enabled	Comments
SC3270	N/A	No known Language Environment dependencies

Pitney Bowes

NAME: Pitney Bowes
ADDRESS: 37 Executive Drive, Danbury, CT 06810-4148
PHONE: (800) 283-1527
WEB SITE: <http://www.pbss.com>

Product	Enabled	Comments
DocSense Mailer's Choice	Version FILE 11: Yes Version FILE 15: No	Product is a Document Distribution product. Product is written in COBOL and Assembler language

Platinum Technology

NAME: Platinum Technology
ADDRESS: 1815 South Meyers Road, Oakbrook Terrace, IL 60181
PHONE: (800) 442-6861
FAX: (800) 442-4230
TECH SUPPORT: (800) 833-PLAT
WEB SITE: <http://www.platinum.com>

Product	Enabled	Comments
DB-EXCEL	Yes	
AION/DS	Yes	
APS HPO	Yes	
TransCentury	Yes	Does not run under VM

Prince Software, Inc.

NAME: Prince Software, Inc.
ADDRESS: 1000C Lake Street, Ramsey, NJ 07446
PHONE: (800) 934-2022
FAX: (201) 934-0220
WEB SITE: <http://www.princesoftware.com>

Product	Enabled	Comments
MHTRAN-1	Yes	
MHTRAN-2	Yes	
Portal 2000	Yes	
Translate/RW	Yes	

Proginet

NAME: Proginet
ADDRESS: 200 Garden City Plaza, Garden City, NY 11530
PHONE: (516) 248-2000
WEB SITE: <http://www.proginet.com>

Product	Enabled	Comments
RPC/EXEC	Yes	
Trans Access Programs and Tools	Yes	

Rocket Software, Inc.

NAME: Rocket Software, Inc.
ADDRESS: 161 Worcester Road, Framingham, MA 01701
PHONE: (508) 875-4321
FAX: (508) 875-1335
WEB SITE: <http://www.rocketsoftware.com>

Product	Enabled	Comments
HPO	Yes	

SAS Institute

NAME: SAS Institute
ADDRESS: 100 SAS Campus Drive, Cary, NC 27513
PHONE: (919) 677-8000
FAX: (919) 677-8123
TECH SUPPORT: (919) 677-8008
WEB SITE: <http://www.sas.com>

Product	Enabled	Comments
MVS-SAS	N/A	
SAS C	No	Cannot be statically linked; but can dynamically load and call a Language Environment/370 application as long as Language Environment/370 requirements for external calls are met. Doesn't support Language Environment headers or calls to Language Environment/370-unique functions.

Seer Technologies, Inc.

NAME: Seer Technologies, Inc.
ADDRESS: 8000 Regency Parkway, Cary, NC 27511
PHONE: (919) 380-5000
FAX: (919) 469-1910
WEB SITE: <http://www.seer.com>

Product	Enabled	Comments
High Productivity System (HPS)	Yes	Generated code is Language Environment-enabled

Serena Software International

NAME: Serena Software International

ADDRESS: 500 Airport Blvd. Second Floor, Burlingame, CA 94010
PHONE: (800) 457-3736 or (415) 696-1800
FAX: (415) 696-1776
TECH SUPPORT: (415) 696-6280
WEB SITE: <http://www.serena.com>

Product	Enabled	Comments
Comparex	N/A	No known Language Environment dependencies
PdsTools	N/A	No known Language Environment dependencies

Software AG

NAME: **Software AG**
ADDRESS: Uhlandstr 12, Darmstadt, Germany D64297 (Software AG Headquarters)
PHONE: (703) 390-9426
 Peter Harris
 Director, IBM Worldwide Technology Alliances
 Peter.Harris@softwareagusa.com
FAX: (703) 390-7401
TECH SUPPORT: Located in multiple countries including the US and Germany
WEB SITE: <http://www.softwareag.com>

Product	Enabled	Comments
Natural DB2 Interface (NDB)	Yes	
Natural CICS Interface (NCI)	Yes	This product has been enabled to support Language Environment under CICS with CICS TS V3.1.
Natural (NAT)	Yes	This product has been enabled for sometime to support Language Environment and has continued to be updated.
Natural Development Server (NDV)	Yes	This product has been enabled for sometime to support Language Environment and has continued to be updated.
EntireX Communicator Broker (EXX)	Yes	Several components of EntireX Communicator Broker are enabled for Language Environment. It is the future plan for all components for EntireX Communicator Broker to be enabled by the end of 2006.

Software Engineers of America (SEA)

NAME: Software Engineers of America (SEA)
ADDRESS: 1230 Hempstead Turnpike, Franklin Square, NY 11010
PHONE: (516) 328-7000
FAX: (516) 354-4015
WEB SITE: <http://www.seasoft.com>

Product	Enabled	Comments
PDSFAST	N/A	No known Language Environment dependencies
FASTVSAM	N/A	No known Language Environment dependencies
FASTGENR	N/A	No known Language Environment dependencies
FDSO	N/A	No known Language Environment dependencies
CODEC	N/A	No known Language Environment dependencies
TRMS	N/A	No known Language Environment dependencies
TAPE2000	N/A	No known Language Environment dependencies
ODDS/MVS	N/A	No known Language Environment dependencies
CSAR	N/A	No known Language Environment dependencies
TRAMS	N/A	No known Language Environment dependencies
JCLPLUS!	N/A	No known Language Environment dependencies
XREFPLUS!	N/A	No known Language Environment dependencies

Sterling Software

NAME: Sterling Software
ADDRESS: 300 Crescent Court, Suite 1200, Dallas, TX 75201
PHONE: (214) 981-1000
FAX: (214) 739-0535
WEB SITE: <http://www.sterling.com>

Product	Enabled	Comments
Directions Image Return	No	A C/S version will replace the current host version
NDM	N/A	Replaced by CONNECT DIRECT

Product	Enabled	Comments
VISION Builder 12.0	Yes	
VISION Inform 2.0	Yes	
VISION Results 3.5	Yes	
VISION Transact 7.0	Yes	
Analysis Design Workstation	Yes	

Stonehouse & Co.

NAME: Stonehouse & Co.
ADDRESS: 4100 Spring Valley Road, Suite 400, Dallas, TX 75244
PHONE: (972) 960-1566
FAX: (972) 770-6909
TECH SUPPORT: (972) 770-6900
WEB SITE: <http://www.ncc.com/stonehouse>

Product	Enabled	Comments
MONIES	Yes	

Syncsort, Inc.

NAME: Syncsort, Inc.
ADDRESS: 50 Tice Blvd., Woodcliff Lake, NJ 07675
PHONE: (201) 930-8200
FAX: (201) 930-8285
TECH SUPPORT: (201) 930-8260
WEB SITE: <http://www.syncsort.com>

Product	Enabled	Comments
Online-SyncSort	Yes	
SyncSort/MVS	Yes	

Texas Instruments, Inc.

NAME: Texas Instruments, Inc.
ADDRESS: 6550 Chase Oaks Blvd., M/S 8474, Plano, TX 75023
PHONE: (214) 575-4553
FAX: (214) 575-4716
WEB SITE: <http://www.ti.com>

Enabled vendor tools

Product	Enabled	Comments
Information Engineering Facility (IEF)	Yes	

Viasoft, Inc.

NAME: Viasoft, Inc.
ADDRESS: 3033 North 44th Street, Phoenix, AZ 85018
PHONE: (800) 525-7775
WEB SITE: <http://www.viasoft.com>

Product	Enabled	Comments
VIA Center	Yes	
VIA/SmartTest	Yes	

Walker Interactive Systems

NAME: Walker Interactive Systems
ADDRESS: 303 Second Street Marathon Plaza Three N, San Francisco, CA 94107
PHONE: (415) 495-8811
FAX: (415) 543-6338
WEB SITE: <http://www.walker.com>

Product	Enabled	Comments
Tamaris	Yes	

Appendix B. Accessibility

Publications for this product are offered in Adobe Portable Document Format (PDF) and should be compliant with accessibility standards. If you experience difficulties when using PDF files, you may view the information through the z/OS Internet Library Web site or the z/OS Information Center. If you continue to experience problems, send an e-mail to mhvrcfs@us.ibm.com or write to:

IBM Corporation
Attention: MHVRCFS Reader Comments
Department H6MA, Building 707
2455 South Road
Poughkeepsie, NY 12601-5400
U.S.A.

Accessibility features help a user who has a physical disability, such as restricted mobility or limited vision, to use software products successfully. The major accessibility features in z/OS enable users to:

- Use assistive technologies such as screen readers and screen magnifier software
- Operate specific or equivalent features using only the keyboard
- Customize display attributes such as color, contrast, and font size

Using assistive technologies

Assistive technology products, such as screen readers, function with the user interfaces found in z/OS. Consult the assistive technology documentation for specific information when using such products to access z/OS interfaces.

Keyboard navigation of the user interface

Users can access z/OS user interfaces using TSO/E or ISPF. Refer to *z/OS TSO/E Primer*, *z/OS TSO/E User's Guide*, and *z/OS ISPF User's Guide Vol I* for information about accessing TSO/E and ISPF interfaces. These guides describe how to use TSO/E and ISPF, including the use of keyboard shortcuts or function keys (PF keys). Each guide includes the default settings for the PF keys and explains how to modify their functions.

z/OS information

z/OS information is accessible using screen readers with the BookServer or Library Server versions of z/OS books in the Internet library at:

<http://www.ibm.com/systems/z/os/zos/bkserv/>

Notices

This information was developed for products and services offered in the U.S.A.

IBM may not offer the products, services, or features discussed in this document in other countries. Consult your local IBM representative for information on the products and services currently available in your area. Any reference to an IBM product, program, or service is not intended to state or imply that only that IBM product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any IBM intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any non-IBM product, program, or service.

IBM may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to:

IBM Director of Licensing
IBM Corporation
North Castle Drive
Armonk, NY 10504-1785
USA

For license inquiries regarding double-byte (DBCS) information, contact the IBM Intellectual Property Department in your country or send inquiries, in writing, to:

IBM World Trade Asia Corporation
Licensing
2-31 Roppongi 3-chome, Minato-ku
Tokyo 106, Japan

The following paragraph does not apply to the United Kingdom or any other country where such provisions are inconsistent with local law:

INTERNATIONAL BUSINESS MACHINES CORPORATION PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some states do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. IBM may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

Any references in this information to non-IBM Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this IBM product and use of those Web sites is at your own risk.

IBM may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Licensees of this program who wish to have information about it for the purpose of enabling: (i) the exchange of information between independently created programs and other programs (including this one) and (ii) the mutual use of the information which has been exchanged, should contact:

IBM Corporation
Mail Station P300
2455 South Road
Poughkeepsie, NY 12601-5400
USA

Such information may be available, subject to appropriate terms and conditions, including in some cases, payment of a fee.

The licensed program described in this information and all licensed material available for it are provided by IBM under terms of the IBM Customer Agreement, IBM International Program License Agreement, or any equivalent agreement between us.

Any performance data contained herein was determined in a controlled environment. Therefore, the results obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurement may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

Information concerning non-IBM products was obtained from the suppliers of those products, their published announcements or other publicly available sources. IBM has not tested those products and cannot confirm the accuracy of performance compatibility or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products.

All statements regarding IBM's future direction or intent are subject to change without notice, and represent goals and objectives only.

This information contains examples of data and reports used in daily business operations. To illustrate them as completely as possible, the examples include the names of individuals, companies, brands, and products. All of these names are fictitious and any similarity to the names and addresses used by an actual business enterprise is entirely coincidental.

COPYRIGHT LICENSE:

This information contains sample application programs in source language, which illustrates programming techniques on various operating platforms. You may copy, modify, and distribute these sample programs in any form without payment to IBM, for the purposes of developing, using, marketing or distributing application programs conforming to the application programming interface for the operating platform for which the sample programs are written. These examples have not been thoroughly tested under all conditions. IBM, therefore, cannot guarantee or imply reliability, serviceability, or function of these programs. You may copy, modify, and distribute these sample programs in any form without payment to IBM for the purposes of developing, using, marketing, or distributing application programs conforming to IBM's application programming interfaces.

If you are viewing this information softcopy, the photographs and color illustrations may not appear.

Policy for unsupported hardware

Various z/OS elements, such as DFSMS, HCD, JES2, JES3, and MVS, contain code that supports specific hardware servers or devices. In some cases, this device-related element support remains in the product even after the hardware devices pass their announced End of Service date. z/OS may continue to service element code; however, it will not provide service related to unsupported hardware devices. Software problems related to these devices will not be accepted for service, and current service activity will cease if a problem is determined to be associated with out-of-support devices. In such cases, fixes will not be issued.

Programming Interface information

This book documents intended Programming Interfaces that allow the customer to write programs to obtain the services of Language Environment in z/OS.

Trademarks

IBM, the IBM logo, and ibm.com are trademarks or registered trademarks of International Business Machines Corp., registered in many jurisdictions worldwide. Other product and service names might be trademarks of IBM or other companies. A current list of IBM trademarks is available on the Web at "Copyright and trademark information" at www.ibm.com/legal/copytrade.shtml.

UNIX is a registered trademark of The Open Group in the United States and other countries.

Java and all Java-based trademarks and logos are trademarks of Sun Microsystems, Inc. in the United States and other countries.

Microsoft, Windows, Windows NT, and the Windows logo are trademarks of Microsoft Corporation in the United States, other countries, or both.

Other product and service names might be trademarks of IBM or other companies.

Bibliography

This section lists the books in the Language Environment library and other publications that may be helpful when using Language Environment.

Language Products Publications

z/OS Language Environment

- *z/OS Language Environment Concepts Guide*, SA22-7567
- *z/OS Language Environment Programming Guide*, SA22-7561
- *z/OS Language Environment Programming Reference*, SA22-7562
- *z/OS Language Environment Customization*, SA22-7564
- *z/OS Language Environment Debugging Guide*, GA22-7560
- *z/OS Language Environment Run-Time Application Migration Guide*, GA22-7565
- *z/OS Language Environment Writing Interlanguage Communication Applications*, SA22-7563
- *z/OS Language Environment Run-Time Messages*, SA22-7566
- *z/OS Language Environment Vendor Interfaces*, SA22-7568
- *z/OS Language Environment Programming Guide for 64-bit Virtual Addressing Mode*, SA22-7569

z/OS XL C/C++

- *z/OS XL C/C++ Language Reference*, SC09-4815
- *z/OS XL C/C++ Compiler and Run-Time Migration Guide for the Application Programmer*, GC09-4913
- *z/OS XL C/C++ Programming Guide*, SC09-4765
- *z/OS XL C/C++ User's Guide*, SC09-4767
- *z/OS XL C/C++ Run-Time Library Reference*, SA22-7821
- *z/OS XL C/C++ Messages*, GC09-4819
- *Standard C++ Library Reference*, SC09-4949

z/OS Metal C Runtime Library

- *z/OS Metal C Programming Guide and Reference*, SA23-2225

Enterprise COBOL for z/OS, V4R2

- *Enterprise COBOL for z/OS, V4R2, Licensed Program Specifications*, GI11-7871
- *Enterprise COBOL for z/OS, V4R2, Customization*, SC23-8526
- *Enterprise COBOL for z/OS, V4R2, Language Reference*, SC23-8528
- *Enterprise COBOL for z/OS, V4R2, Programming Guide*, SC23-8529
- *Enterprise COBOL for z/OS, V4R2, Compiler and Runtime Migration Guide*, GC23-8527

Enterprise COBOL for z/OS, V3R4

- *Enterprise COBOL for z/OS, V3R4, Licensed Program Specifications*, GC27-1411
- *Enterprise COBOL for z/OS, V3R4, Customization*, GC27-1410
- *Enterprise COBOL for z/OS, V3R4, Language Reference*, SC27-1408
- *Enterprise COBOL for z/OS, V3R4, Programming Guide*, SC27-1412
- *Enterprise COBOL for z/OS, V3R4, Compiler and Runtime Migration Guide*, GC27-1409

COBOL for OS/390 & VM

- *COBOL for OS/390 & VM Licensed Program Specifications*, GC26-9044
- *COBOL for OS/390 & VM Customization under OS/390*, GC26-9045

- *COBOL for OS/390 & VM Language Reference*, SC26-9046
- *COBOL for OS/390 & VM Programming Guide*, SC26-9049

Debug Tool

- Debug Tool documentation is available at: <http://www.ibm.com/software/awdtools/debugtool/>

VS FORTRAN Version 2

- *Language Environment for MVS & VM Fortran Run-Time Migration Guide*, SC26-8499
- *Language and Library Reference*, SC26-4221
- *Programming Guide for CMS and MVS*, SC26-4222

Enterprise PL/I for z/OS

- *Enterprise PL/I for z/OS, V3R9, Licensed Program Specifications*, GC27-1455
- *Enterprise PL/I for z/OS, V3R9, Programming Guide*, SC27-1457
- *Enterprise PL/I for z/OS, V3R9, Language Reference*, SC27-1460
- *Enterprise PL/I for z/OS, V3R9, Migration Guide*, GC27-1458
- *Enterprise PL/I for z/OS, V3R9, Messages and Codes*, SC27-1461

PL/I for MVS & VM

- *PL/I for MVS & VM Licensed Program Specifications*, GC26-3116
- *PL/I for MVS & VM Programming Guide*, SC26-3113
- *PL/I for MVS & VM Language Reference*, SC26-3114
- *PL/I for MVS & VM Reference Summary*, SX26-3821
- *PL/I for MVS & VM Compiler and Run-Time Migration Guide*, SC26-3118
- *PL/I for MVS & VM Installation and Customization under MVS*, SC26-3119
- *PL/I for MVS & VM Compile-Time Messages and Codes*, SC26-3229
- *PL/I for MVS & VM Diagnosis Guide*, SC26-3149

High Level Assembler for MVS & VM & VSE

- *Programmer's Guide, MVS & VM Edition*, SC26-4941

Related Publications

CICS

- *CICS Transaction Server for z/OS Installation Guide*, GC34-6224
- *CICS Operations and Utilities Guide*, SC34-6229
- *CICS Problem Determination Guide*, SC34-6239
- *CICS Resource Definition Guide*, SC34-6228
- *CICS Application Programming Guide*, SC34-6231
- *CICS Application Programming Reference*, SC34-6232
- *CICS System Definition Guide*, SC34-6226

DB2

- *Database 2 Application Programming and SQL Guide*, SC26-4377

DFSMS/MVS

- *z/OS MVS Program Management: User's Guide and Reference*, SA22-7643
- *z/OS DFSMS DFM Guide and Reference*, SC26-7395
-

IPCS

- *z/OS MVS IPCS User's Guide*, SA22-7596
- *z/OS MVS IPCS Commands*, SA22-7594
- *z/OS MVS IPCS Customization*, SA22-7595

DFSORT

- *z/OS DFSORT Application Programming Guide, SC26-7523*

IMS/ESA

- *IMS Version 8: Application Programming: Design Guide, SC27-1287*
- *IMS Version 8: Application Programming: Database Manager, SC27-1286*
- *IMS Version 8: Application Programming: Transaction Manager, SC27-1289*
- *IMS Version 8: Application Programming: EXEC DLI Commands for CICS and IMS Version 8, SC27-1288*

z/OS

- *z/OS Introduction and Release Guide, GA22-7502*
- *z/OS Program Directory, GI10-0670*
- *z/OS Planning for Installation, GA22-7504*
- *z/OS Information Roadmap, SA22-7500*
- *z/OS Hot Topics Newsletter, GA22-7501*
- *z/OS Licensed Program Specifications, GA22-7503*

z/OS ISPF

- *z/OS ISPF Dialog Tag Language Guide and Reference, SC34-4824*
- *z/OS ISPF Planning and Customizing, GC34-4814*
- *z/OS ISPF Dialog Developer's Guide and Reference, SC34-4821*

z/OS UNIX System Services

- *z/OS UNIX System Services User's Guide, SA22-7801*
- *z/OS UNIX System Services Command Reference, SA22-7802*
- *z/OS UNIX System Services Programming: Assembler Callable Services Reference, SA22-7803*
- *z/OS UNIX System Services Planning, GA22-7800*

z/OS TSO/E

- *z/OS TSO/E Customization, SA22-7783*
- *z/OS TSO/E Programming Services, SA22-7789*
- *z/OS TSO/E System Programming Command Reference, SA22-7793*

Index

A

Abend-AID 49
accessibility 65
ACF Network Control Program (ACF/NCP) 38
ACF/NCP (ACF Network Control Program) 38
ACF/VTAM for MVS 38
ACF/VTAM for VM 38
AD/Cycle C/370 compiler 38
ADSM (ADSTAR Distributed Storage Manager) 38
ADSTAR Distributed Storage Manager (ADSM) 38
ADW 63
AFP ToolBox for MVS 38
AION/DS 59
AIX Distributed Computing Environment/ESA (DCE/ESA) 38
AMSOFT 44
AMtrust 43
Analysis Design Workstation 63
ANo/MVS 38
ANSYS 44
ANYNET 38
AOC/MVS (Automated Operations Control/MVS) 38
Application Support Facility (ASF) for MVS 39
Application System (AS) 39
APS 55
APS HPO 59
AS (Application System) 39
ASF (Application Support Facility for MVS) 39
ASI-ST 45
ASIM 54
assembler programs
 migrating to Language Environment 19
Automated Operations Control/MVS (AOC/MVS) 38
Automated Systems Information Management 54

B

Basic Telecommunication Access Method (BTAM) 39
BDT (Bulk Data Transfer) 39
BookManager/MVS 39
BookManager/VM 39
BTAM (Basic Telecommunication Access Method) 39
Bulk Data Transfer (BDT) 39

C

C routines
 migrating to Language Environment 17
C/C++ 39
CA-1 48
CA-11 48
CA-7 48
CA-90 48
CA-APC/DOC 46
CA-APCDDS 46
CA-DADS/PLUS 46
CA-Data Query 47
CA-Datacom/CICS Services 46
CA-Datacom/DB 47
CA-Datacom/DB Datadictionary 47
CA-Datacom/DLI Transparency 47
CA-Datacom/Extended SQL Option 46
CA-Datacom/IMS/DC Services 47
CA-Datacom/Total Transparency 47
CA-Datacom/VSAM Transparency 47
CA-DISPATCH 47
CA-DOCVIEW 47
CA-EASYTREVE 47
CA-EXAMINE 47
CA-EZT/DB2 47
CA-EZT/IMS 47
CA-EZT+ 47
CA-EZTEST/CICS/3.4 47
CA-FILESAVE/RCS 47
CA-IDMS 47
CA-INSIGHT/DB2 47
CA-InterTest 5.3 47
CA-JCL/CHECK 47
CA-LIBRARIAN 47
CA-LSERV 48
CA-Masterpiece 48
CA-Netman 48
CA-OPERA 48
CA-OPTIMIZER 48
CA-PANVALET 48
CA-PMO 48
CA-ROSCOE 48
CA-SYMDUMP 48
CA-TELON 48
CA-TLMS 48
CA-VERIFY 48
CACHE RMF Reporter 39
CallFlow 51
CCCA (COBOL CICS Conversion AID) 39
CEEPRMxx parmlib member 6
Change Action 42
CICS Abend-AID 49
CICS/ESA (Customer Information Control System/ESA) 39
CICS/MTCS 39
CICS/MVS 3270 Format Utility 39
CICS/VSAM Recovery 39
CL/GATEWAY 45
CL/SUPERSESSION 45

CLER run-time options report 9
CLIO/S 39
COBOL CICS Conversion AID (CCCA) 39
COBOL programs
 migrating to Language Environment 17
COBOL Structuring Facility 39
CODEC 62
Comparex 61
compatibility
 with previous run-time libraries 15
Compuset 51
Consumer and Merchant Servicing 53
conversion table removal 8
Cross System Product (CSP) 39
CSAR 62
CSP (Cross System Product) 39
Customer Information Control System/ESA (CICS/ESA) 39

D

D CEE 7
Data Base Edit Facility (DBEDIT) 39
Data Correlation and Documentation System 56
Data Facility Sort (DFSORT) 40
Data Interchange 39
DB-EXCEL 59
DB2 39
DBEDIT (Data Base Edit Facility) 39
DCD III 56
DCE/ESA (AIX Distributed Computing Environment/ESA) 38
DCF/MVS (Document Composition Facility) 40
DCF/VM (Document Composition Facility) 40
Deduction Management System 46
Device Support Facility (DSF) 40
DFSMSdfp 40
DFSMSdss 40
DFSMSHsm 40
DFSMSrmm 40
DFSORT (Data Facility Sort) 40
DI/MVS 40
DIR 62
Directions Image Return 62
disability 65
DISOSS 40
DISOSS Library Services Extended (DLS-E) 40
DisplayWrite/370 (DW/370) 40
Distribution Requirements Planning 44
DITTO 40
DLS 51
DLS-E (DISOSS Library Services Extended) 40
DocSense Mailer's Choice 58
DOCU/TEXT 51

Document Composition Facility
(DCF/MVS) 40
Document Composition Facility
(DCF/VM) 40
DPAM 40
DROP/R Capture MVS 40
DSF (Device Support Facility) 40
Dumpmaster 56
DW/370 (DisplayWrite/370) 40

E

E Series (Expert Series) 52
Edge Portfolio Analyzer 52
Emulator Program (EP) 40
Endevor Parallel Development
Manager 48
Endevor/Cross System Product
(Endevor/CSP) 48
Endevor/CSP (Endevor/Cross System
Product) 48
Endevor/DB 48
Endevor/DB2 48
Endevor/MVS 48
EntireX Communicator Broker(EXX) 61
Environment Error Recording
Program 40
EP (Emulator Program) 40
ESCM (ESCON Manager) 40
ESCON Manager (ESCM) 40
Expedite Base 43
Expedite CICS for MVS 43
Expert Series Applications (E Series) 52

F

Falcon 53
FASTGENR 62
FASTVSAM 62
FDSO 62
File-AID/MVS 49
Focus MVS 54
Focus VM 54
Fortran routines
migrating to Language
Environment 17

G

GDDM (Graph Data Display
Manager) 40
GDDM IMD 40
GDDM Program Graphic Feature
(GDDM-PGF) 40
GDDM-PGF (GDDM Program Graphic
Feature) 40
Graph Data Display Manager
(GDDM) 40

H

Hardware Configuration Definition
(HCD) 40
HCD (Hardware Configuration
Definition) 40

HCF (Host Communication Facility) 40
Health Quest 2000 53
High Productivity System 60
Host Communication Facility (HCF) 40
HPO 60
HPS 60

I

IAFC (Item Access Facility
MVS/ESA) 41
IBM Print Services Facility
(PSF/MVS) 40
ICF Catalog Recovery 40
IEF 64
IFPS/Plus (Interactive Financial Planning
System/Plus) 50
IHRS 55
ILC applications
migrating to Language
Environment 16
Image Object Distribution Manager
(IODM) 41
Image/Plus Folder Application Facility
(IPFAF) 41
IMS Application Development Facility
(IMSADF) 40
IMS System Utilities 41
IMS/ESA 41
IMS/ESA Transaction Manager 41
IMSADF (IMS Application Development
Facility) 40
IND\$FILE (PC/TSO File Transfer
Product) 42
INFO/X Enterprise 51
InfoMan 41
INFOPAC-RDS 57
Inforem III 41
Information Engineering Facility 64
Information Management System/ESA
(IMS/ESA) Database Manager 41
Inquire/Text 53
Integral Human Resource System 55
Interactive Financial Planning
System/Plus (IFPS/Plus) 50
Interactive System Product Facility
(ISPF) 41
IODM (Image Object Distribution
Manager) 41
IPFAF (Image/Plus Folder Application
Facility) 41
ISPF (Interactive System Product
Facility) 41
Item Access Facility MVS/ESA
(IAFC) 41

J

JCLPLUS! 62
JES (Job Entry Subsystem) 41
Jes328X Printing Subsystem 41
Job Entry Subsystem (JES) 41
JOB/SCAN 51

K

keyboard 65
KnowledgeTool 41

L

Language Environment 7
migrating from another Language
Environment release 5
planning to migrate to 1
License Power 55

M

M Series (Millennium Series) 52
mainframe
education ix
MAN Series M/TEXT 46
MANTIS 46
MDp (Message Driven processor) 51
Message Driven processor (MDp) 51
MF COBOL 57
MHTRAN-1 59
MHTRAN-2 59
Micro Focus COBOL Workbench 57
migrating
assembler programs to Language
Environment 19
C routines to Language
Environment 17
COBOL programs to Language
Environment 17
Fortran routines to Language
Environment 17
ILC applications to Language
Environment 16
PL/I routines to Language
Environment 18
migration
checklist for 1
from another Language Environment
release 5
from other run-time environments 15
Millennium Series Applications (M
Series) 52
Model 204 49
MONIES 63
MQSeries 41
MRP-8 Manufacturing Resource
Planning 44
MVS-SAS 60
MVS/QuickRef 45
MXG 56

N

NASTRAN 57
Natural (NAT) 61
Natural CICS Interface (NCI) 61
Natural DB2 Interface (NDB) 61
Natural Development Server (NDV) 61
NCP (ACF Network Control
Program) 38
NDM 62

NDM (NetView Distribution Manager) 41
 NetView 41
 NetView Access 41
 NetView Distribution Manager (NDM) 41
 NetView File Transfer Program (NetView FTP) 41
 NetView FTP (NetView File Transfer Program) 41
 NetView Performance Manager (NPM) 41
 NetView/GMFHS 41
 NetView/RODM 41
 Notices 67
 NPM (NetView Performance Manager) 41
 NPSI 41
 NTUNEMON (NCP Monitor Tool) 41
 NTUNENCP (NCP Tuning Tool) 41

O

ODDS/MVS 62
 OfficeVision/MVS 41
 OfficeVision/VM 41
 OGL (Overlay Generation Language/370) 42
 Omegamon for CICS/v300 45
 Omegamon II/v300 45
 Oneware 50
 Online-SyncSort 63
 OS/390 C/C++ 39
 Overlay Generation Language/370 (OGL) 42

P

Page Printing Formatting Aid/370 (PPFA/370) 42
 PagePrinterMigrationProgram (PPMP) 42
 PBA 58
 PC/TSO File Transfer Product (PC/TSO FTP) 42
 PC/TSO FTP (PC/TSO File Transfer Product) 42
 PDSEFAST 62
 PdsTools 61
 Pegasystems Banking Applications 58
 PL/I routines
 migrating to Language Environment 18
 Plus 2000 53
 PM/SS (Programming Maintenance/Standard Solution) 43
 Portal 2000 59
 PPFA/370 (Page Printing Formatting Aid/370) 42
 PPMP
 (PagePrinterMigrationProgram) 42
 Prescient Documentor 52
 Prescient Loadsync 52
 Prescient Replicator 52
 Prexcient Downloader 52
 Print Facility (VMPRF) 42

PRISM 54
 PRISM Investment Management & Accounting 54
 PRO/JCL 50
 Profitmax 53
 Programming Maintenance/Standard Solution (PM/SS) 43
 PSF/MVS (IBM Print Services Facility) 40

Q

QA Center Enterprise Servers 49
 QA Center WebSphere MQ 49
 QAHyperstation 49

R

RAMIS 48
 Resource Measurement Facility (RMF) 42
 RMF (Resource Measurement Facility) 42
 RPC/EXEC 59
 run-time options
 choosing for compatible behavior 21
 comparison between C and Language Environment 21
 comparison between COBOL and Language Environment 22
 comparison between Fortran and Language Environment 24
 comparison between PL/I and Language Environment 25
 differences between 21
 summary and recommendations 26
 run-time options report 7

S

SAS C 60
 SC3270 58
 ScreenView 42
 SearchManager/370 for MVS 42
 SGML Translator 42
 Shelf Space 53
 shortcut keys 65
 Soft Audit/2000 55
 Soft Audit/One 55
 Softswitch Central (MVS/VM) 56
 Spiffy 55
 STROBE 49
 Sunrise 58
 SyncSort/MVS 63
 System Automation for MVS 42
 System Vision Impact Analysis 43
 System Vision JCL VIEW 43
 System Vision Program Inventory 43
 System Vision Upgrade Unit 43
 Systematics Financial & Health Care Packages 44

T

tableBASE 50
 Tamaris 64
 TAPE2000 62
 TAPT 59
 TCP/IP (Transmission Control Protocol/Internet Protocol for VM) 42
 TCP/IP (Transmission Control Protocol/Internet Protocol) 42
 TDS 44
 TDS Healthcare Packages 44
 TICTOC 55
 TRAMS 62
 Trans Access Programs and Tools 59
 TransCentury 59
 Translate/RW 59
 Transmission Control Protocol/Internet Protocol (TCP/IP) 42
 Transmission Control Protocol/Internet Protocol (TCP/IP) for VM 42
 TRMS 62

U

Unicode Services 8

V

VIA Center 64
 VIA/SmartTest 64
 VISION Builder 12.0 63
 VISION Inform 2.0 63
 VISION Results 3.5 63
 VISION Transact 7.0 63
 VisualAge Generator 42
 VisualGen 42
 VisualInfo 42
 VMPRF (Print Facility) 42
 VTAM 38

W

Webb Inquire 53
 WebSphere Abend-AID 49

X

Xpediter/CICS 49
 Xpediter/Code Coverage 49
 Xpediter/IMS 49
 Xpediter/TSO 49
 Xpediter/XChange 49
 XREFPLUS! 62

Z

z/OS 38
 z/OS Basic Skills information center ix
 z/OS UNIX System Services 42



Program Number: 5694-A01

Printed in USA

GA22-7565-11

